

**NEW MEXICO OIL CONSERVATION COMMISSION**  
**Santa Fe, New Mexico**

**HOBBS OFFICE OCC**

**MISCELLANEOUS REPORTS ON WELLS**

**1954 MAY 17 AM 9:53**

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

**Indicate Nature of Report by Checking Below**

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	<b>X</b>
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

May 14th 1954 (Date) Hobbs, New Mexico. (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

**Sunray Oil Corporation**

**A Cooper**

(Company or Operator)

(Lease)

**J P Bum Gibbons**

Well No. **4** in the **SE**  $\frac{1}{4}$  **NE**  $\frac{1}{4}$  of Sec. **12**

(Contractor)

T. **20S R. 36E**, NMPM., **Lumont** Pool, **Lea** County.

The Dates of this work were as follows: **3/23/54 to 5/6/54**

Notice of intention to do the work (was) (~~####~~) submitted on Form C-102 on May 1th 1954, 19....., 19.....  
 (Cross out incorrect words)

and approval of the proposed plan (was) (~~####~~) obtained.

**DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

Hole was filled with heavy mud to kill well, L W Bridge plug set at 3622 in the 7" casing and tested above plug with 2500# No Pressure Drop. Set HOCO C I retainers at 3249 and 2350 and pumped 250 sacks cement thru each. Ran Halliburton retrievable to test 7" and found holes between 110 & 142 and between 448 & 571. Set H R C at 110' and pumped in 200 sacks neat cement 4% gel 30 sacks signalite. Drilled out retainers and cleaned out hole to top of L W Bridge plug at 3622. Ran 89 joints of new 15# A Line casing with Baker float and cemented with 325 sacks neat cement. Circulated out cement. Cement set 48 hours and perforated from L W Log 4 shots per foot 3235 to 3264. Test by el Paso showed 4 million 300 thousand cu ft per day.

Witnessed by A. H. Dulce (Name) Engineer, Sunray Oil Corporation (Company) (Title)

Approved: S. J. Stanley OIL CONSERVATION COMMISSION (Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name A. G. M. Smith

Position Field Sup't

Representing Sunray Oil Corp.

Address Box 128 Hobbs, New Mexico.

Engineer MAY 18 1954

(Title)

(Date)