

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.O.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name State "M"
3. Address of Operator Drawer D, Monument, New Mexico	9. Well No. 2
4. Location of Well UNIT LETTER J, 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 13 TOWNSHIP 20S RANGE 36E NMPM.	10. Field and Pool, or Wildcat Monument-G/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3556' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	well. <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>
OTHER Change status fr. TA to pumping oil <input checked="" type="checkbox"/>			

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to RU pulling unit, run bit to PBD at 3800' & drill out cement to 3803'. Run klustrite shoe & mill over Lynes open hole cement retainer fr. 3803' to 3807'. Run bit & drill cement fr. 3807' to 3865'. Perf. Grayburg San Andres Zone open hole in intervals fr. 3795' to 3850' w/2SPF. Run pkr. set at 3750' & acidize Grayburg San Andres formation fr. 3788' to 3865' w/1500 gal. 15% NEFE acid. Swab load, recover pkr. & run tbg. pump & rods & change status fr. TA'd to pumping oil well.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. L. Whelan Jr. TITLE Supv. Adm. Svc. DATE 6-4-87

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE JUN 3 1987

CONDITIONS OF APPROVAL, IF ANY: