

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation		8. Farm or Lease Name State "M"
3. Address of Operator Drawer D, Monument, NM 88265		9. Well No. 1 2
4. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 13 TOWNSHIP 20 S RANGE 36-E NMPM.		10. Field and Pool, or Wildcat Monument G/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3555' DF		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

October 1977

Pulled production equipment. Set Lynes millable retainer in open hole from 3803' to 3807'. Squeezed Grayburg San Andres Zone in open hole fr 3807' to 3810' w/100 sks class "C" cement w/50 sks in formation and left 50 sks in open hole above retainer, WOC and drilled out cement inside 6-5/8" csg from 3473' to 3778' and open hole to 3800'. Perf Grayburg San Andres Zone in open hole fr 3792' to 3800' w/2 SPF and acidized w/250 gal 15% double inhibited acid. Re-ran production equipment and resumed production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>E. B. Busey</u>	TITLE <u>Supv. Admin. Serv.</u>	DATE <u>11-4-77</u>
APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u>NOV 8 1977</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

7/19/7

OIL CONSERVATION COMM
HOBBS, N. M.