		C-102 and C-103
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE	•	
U.S.G.S.		5a. Indicate Type of Lease
LAND OFFICE		State X Fee
OPERATOR		5. State Oil & Gas Lease No.
CUUDDY NOTI	CEC LUB DEDODTE OU WELL O	mmmmmmm
OD NOT USE THIS FORM FOR PROPOSALS TO	CES AND REPORTS ON WELLS  DIRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.	
USE "APPLICATION FOR PE	TRMIT - " (FORM C-101) FOR SUCH PROPOSALS.)	
I. OIL V GAS	,	7. Unit Agreement Name
WELL A WELL OTHER	₹•	
2. Name of Operator		8. Farm or Lease Name
Amerada Hess Corpora	tion	State "M"
3. Address of Operator	,	9. Well No.
Drawer D, Monument,	NM 88265	, 2
4. Location of Well		10. Field and Pool, or Wildcat
J 1980	FEET FROM THE South LINE AND 1980 FEET FRO	Monument - G/SA ·
UNIT LETTER,	FEET FROM THE SOUTH LINE AND 1980 FEET FROM	THE THE THE THE THE THE
East	13 20 5 36 5	
THE LINE, SECTION	13 TOWNSHIP 20 S RANGE 36 E NMP	
······	V	
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	3555' DF	Lea
Check Appropr	riate Box To Indicate Nature of Notice, Report or C	Ither Data
NOTICE OF INTENTI		NT REPORT OF:
NOTICE OF INTENT	50B3EQ0E	VI REPORT OF:
<u> </u>	[m] [m]	
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	
	OTHER	
OTHER		
	(Clearly state all pertinent details, and give pertinent dates, includi	ng estimated date of starting any proposed
17. Describe Proposed or Completed Operations work) SEE RULE 1103.	(Clearly state all pertinent details, and give pertinent dates, includi	ng estimated date of starting any proposed
work) SEE RULE 1103.	(Clearly state all pertinent details, and give pertinent dates, includi	ng estimated date of starting any proposed
	(Clearly state all pertinent details, and give pertinent dates, includi	ng estimated date of starting any proposed
work) SEE RULE 1103.	(Clearly state all pertinent details, and give pertinent dates, includi	ng estimated date of starting any proposed
August 1977		
August 1977  Squeezed Grayburg Sa	n Andres Zone in open hole from 377	'8' qo 3865' w/200
August 1977  Squeezed Grayburg Sa sks class "C" cement	n Andres Zone in open hole from 377 Drilled out cement to 3810'. Pe	8' go 3865' w/200 rforated Grayburg
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Pepen hole from 3784' to 3804' w/two	8' go 3865' w/200 rforated Grayburg 25 gm glass jet
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Pepen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran survey. Resumed pro	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran r	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran survey. Resumed pro	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran reduction.	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran survey. Resumed pro	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran reduction.	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid. adioactive tracer
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran survey. Resumed pro	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran reduction.	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid.
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran survey. Resumed pro	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran reduction.	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid. adioactive tracer
August 1977  Squeezed Grayburg Sa sks class "C" cement San Andres Zone in o SPF. Acidized Grayb Swabbed water. Ran survey. Resumed pro	n Andres Zone in open hole from 377. Drilled out cement to 3810'. Per pen hole from 3784' to 3804' w/two urg San Andres Zone as above w/2000 temp survey w/150° F. water. Ran reduction.	8' go 3865' w/200 rforated Grayburg 25 gm glass jet gal 15% NE acid. adioactive tracer

CONDITIONS OF APPROVAL, IF ANY:

ON KILL HARRY IN W.