

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SEE INSTRUCTIONS ON REVERSE OF THIS FORM

FORM NO. 9-331
REVISION NO. 1-6-64

SUNDY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		3. LEASE DESIGNATION AND SERIAL NO. 10-10-10
2. NAME OF OPERATOR Continental Oil Company		6. IF INSTANT, ABBREVIATED OR TRUE NAME
3. ADDRESS OF OPERATOR P. O. Box 460, Hobbs, New Mexico 88040		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 330' FWL & 660' FWL, Sec. 14, T-20S, R-36E, Lea County, New Mexico.		8. FARM OR LEASE NAME Eumont 4B-14
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DT, RT, GR, etc.) 3809' CG		10. FIELD AND POOL, OR WILDCAT Eumont Oil Pool
		11. SEC., T., R., S., OR B., AND SURVEY OR AREA Sec. 14, T-20S, R-36E
		12. COUNTY OR PARISH Lea
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) PB & Recompletes ☒	

(Other) ☐ (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well was plugged back from the Monument (G-SA) and recompleted in the Eumont Oil Pool as follows:

1. Cleaned out open hole to 3809'.
2. Set cement plug from 3809-3792'.
3. Ran string shot in open hole 3756-3787, w/300 GR/FT on first run and 500 GR/FT on second run.
4. Set packer at 3726'. Spotted 200 gallons Gypsol in OH Section 3751-3792'. Circulated out Gypsol. Spotted 200 gallons 15% NE-HCL acid over OH 3751-3792'. Acidized OH 3751-3792' w/1300 gallons 15% NE-HCL.

On test 8-3-67, pumped 50 BO, 67 BW, and 86 MOPS in 24 hours.
GOR 1720.

Workover started 7-20-67. Completed 7-25-67.

18. I hereby certify that the foregoing is true and correct

SIGNED Jesse H. Gordon TITLE Supervising Engineer DATE 8-14-67

(This space for Federal or State office use)

APPROVED BY USGS-5 ATL-Ros-2 CHRY-MIA-2 PAN AM-Hobbs-2 PINS TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
AUG 16 1967

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER