

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

RECEIVED OFFICE DEC 3 1958

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

December 1, 1958
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Aztec Oil & Gas Company State E-20-B Well No. 1 in E
(Company or Operator) Lease (Unit)
SW 1/4 NW 1/4 of Sec. 20, T. 20S, R. 36E, NMPM., Eumont Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to plug, pull 5½" casing, and permanently abandon the subject well. A 20 sack cement plug will be placed from 3772' to 3922' to cover existing perforations 3886' to 3922'; a 15 sack cement plug will be placed at the stub end of the cut-off casing; a 25 sack cement plug will be placed from 1900' to 1980' (approx.) to cover the top of the salt at 1980'; a 30 sack cement plug will be placed from 300' to 375' (approx.) to cover the casing shoe of surface pipe at 343'; and a 10 sack cement plug will be placed at the surface. Mud laden fluid will fill the hole between cement plugs. If a known zone of porosity exists between the top of the cut-off casing and the base of the salt this zone will be covered with a cement plug.

Approved..... DEC 2 1958
Except as follows:....., 19.....

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

AZTEC OIL & GAS COMPANY

Company or Operator
Original Signed By

By..... P. R. WATTS, JR.

Position..... District Superintendent
Send Communications regarding well to:

Name..... Aztec Oil & Gas Company
Address..... Box 847, Hobbs, New Mexico