HGY AND MINERALS DE	EPAR	TM
	T	
DISTRIBUTION	1	i
SANTA FE	+-	_
FILE		_
U.1.a.1.		_
LAND OFFICE	_	_
PERATOR	1	-

## JIL CONSERVATION DIVISION

SANTA PE	P. O. BOX 2088	Form C-103	
FILE	SANTA FE, NEW MEXICO 87501	Revised 10-1-78	
U.S.a.S.	7		
LAND OFFICE		5a. Indicate Type of Lease	
OPERATOR	<b>⊣</b>	State Fee X	
	<b>-</b>	5. State Oll & Gas Lease No.	
51,412		2-24 110.	
IDG NOT USE THIS FORM FOR PRI	RY NOTICES AND REPORTS ON WELLS	Alleman	
USE "APPLICAT	TION FOR PERMIT -" FORM C-101) FOR SUCH PROPOSALS.)		
OIL GAS			
WELL X GAS WELL GTHER-		7. Unit Agreement Name	
me of Operator		Eunice Monument Sout	
Chevron U.S.A. Inc.			
dress of Operator		Unit	
P.O. Box 670 Hobb	os NM 00040	0 14 11	
TON OF HODE	75 ; (N) 88240	9. Well No.	
cation of Well		109	
IT LETTER H 1980 FEET FROM THE NORTH LINE AND 660 FEET FR		10. Fleid and Pool, or Wildcat	
•	FEET FROM THE NOT LINE AND 660	Eunice Monument G/SA	
East	25	A CO STORES	
LINE, SECTIO	25 TOWNSHIP 20S RANGE 36E		
mmmmm		·~: (	
	15. Elevation (Show whether DF, RT, GR, etc.)		
3544		12. County	
Check A		Lea	
NOTICE OF W	Appropriate Box To Indicate Nature of Notice, Report of C	Ochon Day	
NOTICE OF IN	ther Data		
	30032002	NT REPORT OF:	
MAN REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WAR		
PARILY ASANDON		ALTERING CASING	
OR ALTER CASING	COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT	
	CHANGE PLANS CASING TEST AND CEMENT JOB		
·	other dpn, log, pe	rf, acdz	
scribe Proposed or Completed Co.			
k) SEE RULE 1 103.	rations (Clearly state all pertinent details, and give pertinent dates, includin		
-	included	e estimated date of starting any proposed	

TD: 3986

POOH w/rods and pump. Establish returns w/air mist. Drlg 4 3/4" hole from 3840 to 3986'. Circ. well clean. Spot 50bbls CKF on bottom. Ran GR, CCL, CNL w/caliper. PU 4" csg gun, perf 5 1/2" csg w/1 JHPF, 180° phased 3681' - 3690'. 9 holes in one run. TIH w/CIBP, set at 3710'. Test CIBP to 1000psi, ok. Released pkr, RDH w/ pkr to 3690'. Spot 84 gallons 15% NEFE HCL across perfs. Swab. Break circulation w/air mist. Drill CIBP at 3710'. Circ hole. TIH w/ 2 3/8" prod. tbg. SN at 3806', EOT at 3822'. Run production equipment. Hung well on beam. Load tbg w/ CKF, tst to 500psi, ok. Rig down unit, clean off location. Turn over to production.

hereby certify that the information above is true and comple	te to the beat of my knowledge and belief.	
ORIGINAL SIGNED BY JERRY SEXTON	THE: Staff Drilling Engr.	May 31, 1988
DISTRICT I SUPERVISOR	TITLE	JUN - 8 1988