

UNIT STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL

LC-048741(B)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

EXXON CORPORATION

3. ADDRESS OF OPERATOR

P.O. Box 1600, MIDLAND, TEXAS 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL AND 1650' FEL, SEC. 26, T-20S, R-36-E.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

L.C. FOPEANO FEDERAL AC 2

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

FUMONT YATES 7 RIVERS
QUEEN11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 26, T-20-S, R-36-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

DF 3571

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

PULL TBG AND HYDROTEST. TBG HAS HOLE IN IT. SPOT ALL CEMENT
PLUGS W/TBG. USE CLASS C NEAT CEMENT FOR PLUGS. PUMP DOWN ALL
PLUGS W/MUD LADEN BRINE (MUD CONSISTENCY TO BE OBTAINED BY MIXING
AT THE RATE OF 25 SK OF CEL PER 100 BBLs. OF BRINE. SPOT A 45 SK PLUG
FROM 3855 TD TO 3620. TAG PLUG TO VERIFY PLACEMENT (MUST BE AT
OR ABOVE 3620'). FREE POINT CUT AND PULL 5 1/2' CSG. CALCULATED TOP
OF CEMENT AT APPROXIMATELY 2620'. CIRCULATE MUD LADEN BRINE
TO SURFACE. SPOT A 20 SK CEMENT PLUG FROM 2900 TO 2800'. SPOT A
30 SK CEMENT PLUG INSIDE AND OUTSIDE 5 1/2" CSG AT CUT POINT. SPOT
A 30 SK CEMENT PLUG FROM 1364 TO 1264'. LEAVE A 10' CEMENT PLUG
AT THE SURFACE. RIG WELLHEAD FOR ABANDONMENT.

APPROVED SUBJECT TO POSSIBLE FUTURE
REQUIREMENT THAT PAD AND/OR ROAD
BE RIPPED AND RELEVELLED

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

UNIT HEAD

DATE

7-24-74

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED

AUG 5 1974

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side