

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API No. 30-025-04153

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. B-2204
7. Unit Agreement Name
8. Farm or Lease Name New
9. Well No. 2
10. Field and Pool, or Wildcat Eunice Monument-Gb/SA
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER-

2. Name of Operator
Phillips Petroleum Company

3. Address of Operator
4001 Penbrook Street, Odessa, Texas 79762

4. Location of Well
UNIT LETTER H, 1980 FEET FROM THE north LINE AND 330 FEET FROM
THE east LINE, SECTION 26 TOWNSHIP 20-S RANGE 36-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3552.2' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Deepen, perforate and treat ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

4-24-87: 3674' PTD. MI & Ru DDU. NU BOP, pressure test to 4000 psi. COOH with tubing.

4-25 & 26-87: Crew off.

4-27 thru

5-04-87: Drld out CIBP at 3785'. Drld out hole to 3881'.

5-05-87: Perf'd open hole with 1JSPF from 3735'-3790' & 3815'-3860'.

5-06 thru

5-11-87: Treated Grayburg open hole interval 3701'-3881' with 3000 gals of 15% NEFE HCL acid. Swbd 6 hrs, 7 BO, 50 BW.

5-12 thru

5-17-87: Swbd 24 hrs, 22 BO, 18 BLW. Frac'd open hole w/40,000 gals Versagel 1300 w/29,000# 20/30 mesh sand and 65,000# 12/20 mesh sand. SD 24 hrs.

5-18-87: Swbd 11 hrs, rec 29 BO, 34 BW.

SEE REVERSE SIDE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Engineering Supervisor, Reserve DATE June 5, 1987

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE JUN 11 1987

5-19-87: Swbd 7 hrs, 35 BO, 19 BW.

5-20-87: Set 2-3/8" tbg, SN at 3810'. ran 2" x 1 1/2" x 16' insert pump & rods.
Pmpd 14 hrs, no gauge.

5-21 thru

5-27-87: Repaired pump. Pmpd 48 hrs, 93 BO, 20 BW.

5-28-87: Pmpd 24 hrs, 51 BO, 8 BW, GOR 2431, 124 MCFC from open hole 6710'-3881'.
Job complete.

RECEIVED
JUN 9 1987
OCD
HOBBS OFFICE