

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New MexicoHOBBS OFFICE OCC
1957 OCT 29 AM 11:02

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)October 29, 1957
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Charles P. Miller Miller State Well No. 1 in I
(Company or Operator) (Unit)
NE $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 29, T. 20 S., R. 36 E. NMPM., Eumont Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well has proven to be non-commercial in that it pumps only 2 barrels of oil and 35 barrels salt water per day. We therefore ask permission to abandon it on the following procedure. A Baker bridging plug was set at 3898 and the hole above this point to a depth of 3866' has been filled in successive stages with cement, Calseal, and Hydromite. Perforations are open from 3843' to 3852'. These perforations were washed with mud acid by a surface pressure on tubing of 3100# and an injection rate of 1 barrel per minute. Hole was then swabbed dry; allowed to stand 44 hours and still found to be dry. We therefore propose to cover these perforations by dumping 3 sacks of cement on top of the present Hydromite plug at 3866'. We will then shoot off as much 5½" casing as possible above our cement top of 2590'. We will then pull 5½" casing and thereafter set a 3 sack cement plug at base of 8-5/8" casing which is cemented at 365'. (Cement circulated back into cellar on 8-5/8") We will then set the regulation marker in a cement plug at surface after which we will clear the surface around the well site and leave it in an orderly condition.

In accordance with regulations we will fill the hole with heavy mud.

Approved....., 19.....
Except as follows:By Charles P. Miller
Company or OperatorPosition Owner
Send Communications regarding well to:Approved
OIL CONSERVATION COMMISSIONBy E. Fischer Name Charles P. MillerTitle..... Address Box 385, Hobbs, New Mexico.