

NEW MEXICO OIL CONSERVATION COMMISSION
HOBBS OFFICE, OCC
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

| | | | | | |
|---|-------------------------------------|--|-------------------------------------|---|-----------|
| NOTICE OF INTENTION TO CHANGE PLANS | | NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL | | NOTICE OF INTENTION TO DRILL DEEPER | |
| NOTICE OF INTENTION TO PLUG WELL | | NOTICE OF INTENTION TO PLUG BACK | <input checked="" type="checkbox"/> | NOTICE OF INTENTION TO SET LINER | |
| NOTICE OF INTENTION TO SQUEEZE | | NOTICE OF INTENTION TO ACIDIZE | | NOTICE OF INTENTION TO SHOOT (Nitro) | |
| NOTICE OF INTENTION TO GUN PERFORATE | <input checked="" type="checkbox"/> | NOTICE OF INTENTION (OTHER) | | NOTICE OF INTENTION (OTHER) | Acidizing |

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

October 2, 1957
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Charles F. Miller (Company or Operator) Miller State Well No. 1 in 1 (Unit)
NE 1/4 SE 1/4 of Sec. 29, T. 20S, R. 36E, NMPM, Kament Pool
(40-acre Subdivision)
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We set a Baker Drillable bridging plug at depth of 3898' and dumped four feet of Hydromite on top of plug. We then perforated casing with four holes per foot between depths 3873' and 3878'. We then washed this perforated section with 500 gallons Mud acid. Section treated with maximum of 600 pounds surface pressure. We snubbed well dry and allowed it to stand 44 hours. We then ran the snub again and found hole to be completely dry.

We now propose to plug back with three sacks of Calceal and cap this plug with four feet of Hydromite. We plan for a total plug back to 3870'. We will then perforate a section from 3843' to 3852' with four bullet holes per foot. This perforation will be made in a "dry" hole and should there be any gas or oil in the section to be perforated, it should show readily in the hole when perforations are made.

If results from shooting are favorable we will wash the perforations with 500 gallons of mud acid then snub the hole. If snubbing test gives favorable results we will fracture through perforations with 5000 gallons "frac" and 1/2 sand per gallon.

Approved....., 19.....
Except as follows:

Charles F. Miller
Company or Operator
By.....

Position..... Owner
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By.....

Name..... Charles F. Miller

Title.....

Address..... Box 385, Hobbs, New Mexico.