K

UNITED STATES

Form 9-881a (Feb. 1951)

NOTICE OF INTENTION TO DOWN	A CURCULAR PERCENT OF WATER CHAPTER
NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE PL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO TEST WATE	The state of the s
NOTICE OF INTENTION TO RE-DRILL ([II
NOTICE OF INTENTION TO SHOOT OR	
NOTICE OF INTENTION TO PULL OR A	
NOTICE OF INTENTION TO ABANDON N	WELL
(INDICAT	TE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
/ell No is locate	ed 1983 ft. from ${3 \choose S}$ line and 1983 ft. from ${W \choose W}$ line of sec.
III/h Su/h Sec. 3h	(Twp.) (Range) (Meridian)
Banant	Les New Nexton
(Field)	(County or Subdivision) (State or Territory)
	DETAILS OF WORK
A . A A	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joing points, and all other important proposed work)
evised for error in less plan to drill with a	objective sands; show sizes, weights, and lengths of proposed casings: indicate mudding in
	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joing points, and all other important proposed work) coation. Original submitted August 8, 1955. retary tools to an approximate depth of 3950; for a case. At approximately 250; we plan to run 8-5/8° 0.
evised for error in le e plan to drill with a n the Tatos-Seven Rive -55 coming and commit	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joing points, and all other important proposed work) coation. Original submitted August 8, 1955. retary tools to an approximate depth of 3950' for over. At approximately 250' we plan to run 8-5/8" 0 with 250 seeks. We plan to run 5-1/2" 0.D. list N-
evised for error in le e plan to drill with a n the Yster-Seven Rive -55 casing and essent e T.D. and essent with	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joint points, and all other important proposed work) coation. Original submitted August 8, 1955. retary tools to an approximate depth of 3950' for ore. At approximately 250' we plan to run 8-5/8" 0 with 250 seeks. We plan to run 5-1/2" 0.D. list N-1, 500 seeks. Three drill sten tests are to be taken
evised for error in le e plan to drill with a n the Yates-Seven Rive -55 casing and coment e T.D. and coment with ppreximately 3520' to outron log and perform	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joint points, and all other important proposed work) continu. Original submitted August 8, 1955. retery tools to an approximate depth of 3950' for core. At approximately 250' we plan to run 8-5/8" 0 with 250 seeks. We plan to run 5-1/2" 0.D. list Hand Soo seeks. Three drill stem tests are to be take T.D. After casing has been set we plan to run a gate opposite the pay sones as determined by logs and
evised for error in he plan to drill with a the Tatos-Seven Rive-55 casing and essent of T.D. and conent with approximately 3520' to cution log and performant fracture of approximately send fracture of approximately s	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joing points, and all other important proposed work) coation. Original submitted August 8, 1955. retary tools to an approximate depth of 3950' for a case. At approximately 250' we plan to run 8-5/8" 0 with 250 seeks. We plan to run 5-1/2" 0.D. lb/ N-1 500 seeks. Three drill sten tests are to be take T.D. After easing has been set we plan to run a gate opposite the pay sones as determined by logs an reminately 5000 gallens of oil with 1/ of sand per
evised for error in he plan to drill with a the Tatos-Seven Rive-55 casing and coment of T.D. and coment with ppreximately 3520° to outron log and perform	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joing points, and all other important proposed work) coation. Original submitted August 8, 1955. retary tools to an approximate depth of 3950' for a case. At approximately 250' we plan to run 8-5/8" 0 with 250 seeks. We plan to run 5-1/2" 0.D. lb/ N-1 500 seeks. Three drill sten tests are to be take T.D. After easing has been set we plan to run a gate opposite the pay sones as determined by logs an reminately 5000 gallens of oil with 1/ of sand per
e plan to drill with an the Tator-Seven River-55 coming and commute T.D. and commute with a presentably 3520° to make a log and perference and fracture of apple to be used if necessary	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joing points, and all other important proposed work) contien. Original submitted August 8, 1955. retary tools to an approximate depth of 3950' for ore. At approximately 250' we plan to run 8-5/8" (with 250 seeks. We plan to run 5-1/2" 0.D. light N-100 seeks. Three drill stem tests are to be take T.D. After casing has been set we plan to run a gate opposite the pay source as determined by logs an regimately 5000 gallens of oil with 14 of sand per 7.
e plan to drill with a m the Tatos-Seven Rive -55 cosing and coment e T.D. and coment with ppreximately 3520° to cutton log and perfer sund fracture of appl e be used if necessary	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joing points, and all other important proposed work) coation. Original submitted August 8, 1955. retary tools to an approximate depth of 3950' for a case. At approximately 250' we plan to run 8-5/8" 0 with 250 seeks. We plan to run 5-1/2" 0.D. lb/ N-1 500 seeks. Three drill sten tests are to be take T.D. After easing has been set we plan to run a gate opposite the pay sones as determined by logs an reminately 5000 gallens of oil with 1/ of sand per
e plan to drill with a the Tator-Seven Rive-55 casing and coment with a T.D. and coment with approximately 3520' to series log and perform tend fracture of approximately if necessary a request permission to	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joint points, and all other important proposed work) continu. Original submitted August 8, 1955. retery tools to an approximate depth of 3950 for core. At approximately 250 we plan to run 8-5/8 0 with 250 seeks. We plan to run 5-1/2 0.D. list Hand 500 seeks. Three drill stem tests are to be take T.D. After easing has been set we plan to run a gate opposite the pay sones as determined by logs an reminately 5000 gallens of oil with 1s of send per years of the drill this well and to produce it on completion.
plan to drill with a the Tatop-Seven Rive-SS casing and coment with a T.D. and coment with approximately 3520' to entron log and performant fracture of approximately if necessary to request permission to	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joing points, and all other important proposed work) contien. Original submitted August 8, 1955. retary tools to an approximate depth of 3950' for ore. At approximately 250' we plan to run 8-5/8" (with 250 seeks. We plan to run 5-1/2" 0.D. light N-100 seeks. Three drill stem tests are to be take T.D. After casing has been set we plan to run a gate opposite the pay source as determined by logs an regimately 5000 gallens of oil with 14 of sand per 7.
plan to drill with a the Tator-Seven Rive-55 casing and commt viti pproximately 3520' to make a log and performand fracture of apply be used if necessary request permission to understand that this plan of work:	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joint points, and all other important proposed work) coation. Original submitted August 5, 1955. retery tools to an approximate depth of 3950 for core. At approximately 250 we plan to run 8-5/8 0 with 250 seeks. We plan to run 5-1/2 0.D. list find 500 seeks. We plan to run 5-1/2 0.D. list find 500 seeks. Three drill stem tests are to be take T.D. After easing has been set we plan to run a gate opposite the pay sones as determined by logs an reminately 5000 gallens of oil with 1s of sand per to drill this well and to produce it on completion. must receive approval in writing by the Geological Survey before operations may be communicated approval in writing by the Geological Survey before operations may be communicated.
plen to drill with a the Tator-Seven Rive-55 casing and count vita proximately 3520' to make log and performant fracture of approximately permission to used if necessary to request permission to understand that this plan of work to make the permission of the attention to the plan of work to make the plan of the pla	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joint points, and all other important proposed work) contien. Original submitted August 5, 1955. retery tools to an approximate depth of 3950' for case. At approximately 250' we plan to run 5-5/8" 0 with 250 seeks. We plan to run 5-1/2" 0.D. list H-1 500 seeks. We plan to run 5-1/2" 0.D. list H-1 500 seeks. Three drill sten tests are to be take T.D. After easing has been set we plan to run a gate opposite the pay sones as determined by logs an regimetely 5000 gallens of oil with 1s of sand per y. te drill this well and to produce it on completion. must receive approval in writing by the Geological Survey before operations may be committee Refining Company
plan to drill with a the Tatop-Seven Rive-S casing and commit of T.D. and commit with approximately 3520' to nation log and performant fracture of approximately if necessary be used if necessary to request permission to understand that this plan of work is a permission of the permi	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joint points, and all other important proposed work) contien. Original submitted August 5, 1955. retery tools to an approximate depth of 3950' for case. At approximately 250' we plan to run 5-5/8" 0 with 250 seeks. We plan to run 5-1/2" 0.D. list H-1 500 seeks. We plan to run 5-1/2" 0.D. list H-1 500 seeks. Three drill sten tests are to be take T.D. After easing has been set we plan to run a gate opposite the pay sones as determined by logs an regimetely 5000 gallens of oil with 1s of sand per y. te drill this well and to produce it on completion. must receive approval in writing by the Geological Survey before operations may be committee Refining Company
plen to drill with a the lates-Seven Rive-S casing and coment with presidentely 3520° to make a log and perfers and fracture of apple to used if necessary to request permission to make the permission of the lates and the lates are lates and lates and lates are lates are lates and lates are lates are lates and lates are lates	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joint points, and all other important proposed work) contien. Original submitted August 8, 1955. retery tools to an approximate depth of 3950' for core. At approximately 250' we plan to run 8-5/8" 0 with 250 seeks. We plan to run 5-1/2" 0.D. lb/ H-h 500 seeks. Three drill stem tests are to be take T.D. After easing has been set we plan to run a gate opposite the pay sones as determined by logs an reminately 5000 gallens of oil with lf of send per to drill this well and to produce it on completion. must receive approval in writing by the Geological Survey before operations may be committee. Refining Company
plan to drill with a the Tates-Seven Rive 55 casing and coment with premientally 3520' to when log and performant fracture of appropriately permission in the west permission in the seven log and performant fracture of appropriately permission in the seven log and performant fracture of appropriately permission in the seven log and permission in the	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joint points, and all other important proposed work) contien. Original submitted August 8, 1955. retery tools to an approximate depth of 3950' for core. At approximately 250' we plan to run 8-5/8" 0 with 250 seeks. We plan to run 5-1/2" 0.D. light from 1500 seeks. Three drill stem tests are to be take T.D. After easing has been set we plan to run a gate opposite the pay sones as determined by logs an reminately 5000 gallens of oil with light send per to drill this well and to produce it on completion. must receive approval in writing by the Geological Survey before operations may be committee. Refining Company
plan to drill with a the Tates-Seven Rive 55 casing and essent with presidentely 3520' to when log and perfers and fracture of apple to used if necessary request permission and understand that this plan of work ampany the Atlant dress Rev. 871.	objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding joints, and all other important proposed work) coation. Original submitted August 8, 1955. retery tools to an approximate depth of 3950° for ores. At approximately 250° we plan to run 8-5/8° 0° with 250 seeks. We plan to run 5-1/2° 0.D. lief N-1, 500 seeks. Three drill sten teste are to be take T.D. After casing has been set we plan to run a gate opposite the pay sones as determined by logs as resimately 5000 gallens of oil with 1/ of send per to drill this well and to produce it on completion. must receive approval in writing by the Geological Survey before operations may be committee. Refining Company

U. S. GOVERNMENT PRINTING OFFICE 16-8437-5