



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

Gulf Oil Corporation
(Company or Operator)

R. R. Bell "T"
(Lessee)

Well No. 2, in SE 1/4 of NW 1/4, of Sec. 34, T. 20-S, R. 36-E, NMPM.
Eumont Pool, Lea County.

Well is 1980 feet from North line and 1980 feet from West line
of Section 34-20-36. If State Land the Oil and Gas Lease No. is B-230-1

Drilling Commenced March 25, 1955. Drilling was Completed April 8, 1955.

Name of Drilling Contractor Howard P. Holmes Drilling Cont.

Address Box 667, Hobbs, N. M.

Elevation above sea level at Top of Tubing Head 3588'. The information given is to be kept confidential until _____, 19_____.

OIL SANDS OR ZONES

No. 1, from 3745 to 3885' No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.

No. 2, from _____ to _____ feet.

No. 3, from _____ to _____ feet.

No. 4, from _____ to _____ feet.

CASING RECORD

| SIZE | WEIGHT PER FOOT | NEW OR USED | AMOUNT | KIND OF SHOE | CUT AND PULLED FROM | PERFORATIONS | PURPOSE |
|--------|-----------------|-------------|--------|--------------|---------------------|--------------|--------------|
| 9-5/8" | 32.30# | New | 323' | Baker | | | Surface Pipe |
| 7" | 20# | New | 3763' | Howco | | 3745-3770' | Prod. String |
| | | | | | | | |

MUDDING AND CEMENTING RECORD

| SIZE OF HOLE | SIZE OF CASING | WHERE SET | NO. SACKS OF CEMENT | METHOD USED | MUD GRAVITY | AMOUNT OF MUD USED |
|--------------|----------------|-----------|---------------------|-------------|-------------|--------------------|
| 12-1/4" | 9-5/8" | 337' | 275 | Howco P & P | | |
| 8-3/4" | 7" | 3780' | 1650 | " " " " | | |
| | | | | | | |

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

SEE ATTACHED SHEET

Result of Production Stimulation Flowed 9 bbls oil, no water thru 2-3/8" tubing in 24 hours.

Depth Cleaned Out _____

COORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3885 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing December 9, 1955

OIL WELL: The production during the first 24 hours was 9 barrels of liquid of which 100% was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity 24

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

| Southeastern New Mexico | | | Northwestern New Mexico | | |
|-------------------------|-------|--|-------------------------|--|-----------------------|
| T. Anhy. | 1691' | | T. Devonian | | T. Ojo Alamo |
| T. Salt | | | T. Silurian | | T. Kirtland-Fruitland |
| B. Salt | 3147 | | T. Montoya | | T. Farmington |
| T. Yates | 3340 | | T. Simpson | | T. Pictured Cliffs |
| T. 7 Rivers | 3805 | | T. McKee | | T. Menefee |
| T. Queen | | | T. Ellenburger | | T. Point Lookout |
| T. Grayburg | | | T. Gr. Wash | | T. Mancos |
| T. San Andres | | | T. Granite | | T. Dakota |
| T. Glorieta | | | T. | | T. Morrison |
| T. Drinkard | | | T. | | T. Penn. |
| T. Tubbs | | | T. | | T. |
| T. Abo | | | T. | | T. |
| T. Penn. | | | T. | | T. |
| T. Miss. | | | T. | | T. |

FORMATION RECORD

| From | To | Thickness in Feet | Formation | From | To | Thickness in Feet | Formation |
|------|------|----------------------|--|------|----|----------------------|-----------|
| 0 | 13' | | Distance from Kelly Drive Bushing to Ground | | | | |
| | 135 | | Surface Sand & Caliche | | | | |
| | 340 | | Red Bed | | | | |
| | 1569 | | Red Bed & Shells | | | | |
| | 1690 | | Red Bed | | | | |
| | 1919 | | Anhydrite & Gypsum | | | | |
| | 3151 | | Salt & Anhydrite | | | | |
| | 3257 | | Anhydrite | | | | |
| | 3755 | | Lime & Anhydrite | | | | |
| | 3784 | | Lime | | | | |
| | 3835 | | Sand, Dolomite & Shale | | | | |
| | 3885 | | Sand & Dolomite | | | | |

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

December 30, 1955 (Date)
Company or Operator Gulf Oil Corporation Address Box 2167, Hobbs, N. M.
Name J. H. Russell Position or Title Asst. Area Supt. of Prod.