

Attachment - C-105

Gulf Oil Corporation - R. R. Bell "I" No. 2-F, 34-20-36

RECORD OF PRODUCTION AND STIMULATION

4-9-55 - Washed formation from 3780-3885' with 500 gallons mud acid.
Reversed out.

4-10-55 - Treated formation from 3780-3885' with 1000 gallons 15% NE acid.
Average injection rate 65 gallons per minute.

4-10-55 - Treated open hole formation from 3780-3885' with 15,000 gallons
24 gr. oil with 1# sand per gallon. Average injection rate 12 bbls per minute.

5-13-55 - Treated perforations in 7" casing from 3745-3770' with 500 gallons
mud acid. Washed by perforations then pumped into formation. Average injection
rate 5 gallons per minute.

5-14-55 - Treated perforations in 7" casing from 3745-3770' with 5000 gallons
24 gr. oil with 1# sand per gallon. Average injection rate 9.3 bbls per minute.

DEVIATIONS - TOTCO SURVEYS

3/4 - 325'	1-1/2 - 1880
3/4 - 1035	1-1/4 - 1938
1/2 - 1220	1-3/4 - 2033
3/4 - 1400	1-1/2 - 2127
1-1/2 - 1688	1-1/2 - 2215
1-3/4 - 1752	