

COPY TO O. G. HOBBS

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. W 07966

Unit 200

RECEIVED

AUG 12 1954

U. S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 10, 1954

The Bay Pet. Corp.
Well No. 21 Fed. is located 660 ft. from N line and 3000 ft. from W line of sec. 35

NE 1/4 of Section 35 (1/4 Sec. and Sec. No.)
2-20-4 (Twp.) 2-16-4 (Range) 10N (Meridian)
1900 Section Monument (Field) Los Alamos (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 3500 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill a Queen Sand test to approximately 4200 feet. All casing, cementing and shut off tests will be in accordance with the approved methods of the U.S.G.S.

Casing program: 8-5/8" to 300' cemented with 300 sacks
5-1/2" to 4200' cemented with 600 sacks

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The Bay Petroleum Corporation

Address 217 West Wall Street

Midland, Texas

By

J. D. McLean
Geologist

Title

