

AREA 640 ACRES
LOCATE WELL CORRECTLYNEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

The Texas Company Box 1720, Ft. Worth 1, Texas
Company or Operator Address
Z. A. McMillan "B" Well No. 1 in NW 1/4 SE 1/4 of Sec. 4, T. 19-S.
Lease
R. 37-E, N. M. P. M. Monument Field, Lea County.
Well is 1650 feet south of the North line and 1650 feet west of the East line of Sec. 4.
If State land the oil and gas lease is No. -- Assignment No. --
If patented land the owner is Z. A. McMillan Address Box 782, Hobbs, N.M.
If Government land the permittee is -- Address --
The Lessee is The Texas Company Address Houston, Texas
Drilling commenced September 8, 1949 Drilling was completed September 21, 1949
Name of drilling contractor Livermore Drilling & Exploration, Ltd. Address Box 191, Lubbock, Texas
Elevation above sea level at top of casing 3675 feet.
The information given is to be kept confidential until -- 19 --

OIL SANDS OR ZONES

No. 1, from 2780 to 3200 (G) No. 4, from -- to --
No. 2, from -- to -- No. 5, from -- to --
No. 3, from -- to -- No. 6, from -- to --

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from -- to -- feet.
No. 2, from -- to -- feet.
No. 3, from -- to -- feet.
No. 4, from -- to -- feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8-5/8	28#	8RT	Smls.	272	Baker	--	-	-	-
8-5/8	32#	8RT	Smls.	21					
5-1/2	14#	8RT	Smls.	2793	Hallib.	--	-	-	-

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
12-1/4	8-5/8	301	200	Hallib	--	--
7-7/8	5-1/2	2780	300	Hallib		

PLUGS AND ADAPTERS

Heaving plug—Material -- Length -- Depth Set --
Adapters — Material -- Size --

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
Neither shot nor acidized						

Results of shooting or chemical treatment --
--
--

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3200 feet, and from -- feet to -- feet.
Cable tools were used from -- feet to -- feet, and from -- feet to -- feet.

PRODUCTION

Put to producing --, 19 --
The production of the first 24 hours was -- barrels of fluid of which -- % was oil; -- % emulsion; -- % water; and -- % sediment. Gravity, Be --
If gas well, cu. ft. per 24 hours 2,630,000 Gallons gasoline per 1,000 cu. ft. of gas --
Rock pressure, lbs. per sq. in. 1448#

EMPLOYEES

L. A. Greene Driller R. L. Gann Driller
J. R. Franks Driller J. M. Cason Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 14th day of November, 1949
Notary Public
My Commission expires June 1, 1951
Midland, Texas November 14, 1949
Name: [Signature]
Position: Dist. Supt.
Representing: The Texas Company
Company or Operator
Address: Box 1270, Midland, Texas

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	70	70	Rock, Gravel & Sand
70	315	245	Sand & Shale
315	1100	785	Red Beds
1100	1400	300	Red Beds & Shale
1400	1610	210	Red Beds
1610	1690	80	Anhy & Shale
1690	1790	100	Salt & Anhy
1790	1910	120	Salt, Anhy & Shale
1910	2650	740	Anhy & Salt
2650	2863	213	Lime & Anhy
2863	2929	66	Lime
2929	2970	41	Lime & Anhy
2970	2985	15	Lime
2985	2990	5	Sand
2990	3002	12	Lime & Anhy
3002	3005	3	Sand
3005	3035	30	Lime
3035	3042	7	Sand
3042	3140	98	Lime & Anhy
3140	3193	53	Lime & Sand
3193	3200	7	Lime & Anhy
3200 Total Depth			

All measurements from rotary table or 10' above ground.

Deviation Tests

550	3/4
800	1
1045	3/4
1232	1
1634	3/4
1831	1
2060	3/4
2350	1/2
2630	0
2780	1/4

2" EUE tubing run to 3099'.

Open-flow volume test 10-11-49, 2,630 MCF