

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other NIO Well

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 730, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL &amp; 1652' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) Test Casing ☐

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☐

(X)

APR 19 1983

OIL & GAS  
MINERALS MGMT. SERVICE  
ROSWELL, NEW MEXICO

LEASE

NM-02053

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

East Eumont Unit

8. FARM OR LEASE NAME

9. WELL NO.

13

10. FIELD OR WILDCAT NAME

Eumont

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 4, T-19S, R-37E

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3703' DF

Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4/5/83 Rig up. Ran RTTS pkr to 1620'. Pkr set down. Pull pkr. Ran 3 5/8" bit & csg scrapper to 1930'. Rig up reverse unit. Clean out to 2418'.

4/6/83 Clean out 2418-3569'. Pull bit. Ran RTTS to 3548'. Locate hole 2101-2153'. Pull pkr.

4/8/83 Ran Howco CI plug & stop @ 2152'. Pulled plug ran tbg open end. Spot 12 sxs of sand 3958-3845'. Spot 25 sxs of class "C" 3845-3425'. Pulled tbg 2025'.

4/9/83 Ran 2 3/8" open end set down @ 2199'. Pulled tbg. Ran 3 5/8" bit. Set down 2195' to 2202'. Pulled bit.

4/11/83 Lay down 2 3/8" tbg, Howco cemented w/ 890 sxs class "C" down 4 1/2" csg, hole @ 2153'. Circ to surface, 4 1/2" full of cement. Rig down. T&A.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D.R. Crockett TITLE Area Superintendent DATE April 18, 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD

SEP 12 1983