NEW MEXICO OIL CONSERVATION COMMISSION

Santa, Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	X
NOTICE OF INTENTION TO DEEPEN WELL		
Odessa,	Texas. March 23, 1939	
DIL CONSERVATION COMMISSION,	Flace Date	
Santa Fe, New Mexico.	LUILINKE	
Gentlemen:		
Following is a notice of intention to do certain work as	Well No. 1 in NE/	4 of SW/
of Sec. 7, T. 19 S, R. 37 E	-, N. M. P. M., Monument	Field,
LeaCounty.		
FULL DETAILS OF PR	OPOSED PLAN OF WORK	
FOLLOW INSTRUCTIONS IN THE RULE	S AND REGULATIONS OF THE COMMISSION	
(1) Load hole with mu (2) Cement through tu	bing from bottom (4069) to 7" c	asing
(2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30'.	bing from bottom (4069) to 7" c l as much 7" as pessible. With heavy mud and bridge at ap	
(2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded	bing from bottom (4069) to 7" c l as much 7" as pessible. With heavy mud and bridge at ap	
(2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30'.	bing from bottom (4069) to 7" c l as much 7" as pessible. with heavy mud and bridge at ap th cement.	
(2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30'.	bing from bottom (4069) to 7" c 1 as much 7" as pessible. with heavy mud and bridge at ap ith cement. MAR 29 1939	
(2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30'.	bing from bottom (4069) to 7" c l as much 7" as pessible. with heavy mud and bridge at ap th cement. MAR 29 1939	
 (2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30. (5) Fill to surface w 	bing from bottom (4069) to 7" c 1 as much 7" as pessible. with heavy mud and bridge at ap ith cement. MAR 29 1939	
(2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30'.	bing from bottom (4069) to 7" c l as much 7" as pessible. with heavy mud and bridge at ap with cement. MAR 29 1939 HOBBS OFFICE	
(2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30. (5) Fill to surface w MAR 29 1939	bing from bottom (4069) to 7" c 1 as much 7" as pessible. With heavy mud and bridge at ap th cement. MAR 29 1939 HOBBS OFFICE Great Western Producers. Inc	
 (2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30. (5) Fill to surface w 	bing from bottom (4069) to 7" c 1 as much 7" as pessible. With heavy mud and bridge at ap th cement. MAR 29 1939 HOBBS OFFICE Great Western Producers. Inc	
(2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30. (5) Fill to surface w MAR 29 1939	bing from bottom (4069) to 7" c 1 as much 7" as pessible. with heavy mud and bridge at ap with cement. MAR 29 1939 HOBBS OFFICE Great Western Producers, Inc Mark 29 Mark 20 HOBBS OFFICE	
(2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30. (5) Fill to surface w MAR 29 1939	bing from bottom (4069) to 7" c 1 as much 7" as pessible. with heavy mud and bridge at ap with cement. MAR 29 1939 HOBBS OFFICE Great Western Producers, Inc Company op Operation, MAR 2000000000000000000000000000000000000	
(2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30. (5) Fill to surface w MAR 29 1939	bing from bottom (4069) to 7" c 1 as much 7" as pessible. with heavy mud and bridge at ap with cement. MAR 29 1938 HOBBS OFFICE Great Western Producers, Inc By Position	
(2) Cement through tu seat (3828). (3) Shoot off and pul (4) Leave hole loaded 30. (5) Fill to surface w MAR 29 1939 Approved, 19	bing from bottom (4069) to 7" c l as much 7" as pessible. with heavy mud and bridge at ap with cement. MAR 29 1939 HOBBS OFFICE Great Western Producers, Inc Company on Operating By Position Send communications regarding well to	

u/

Title

-+-)f1_- &

AS INSPECTOR