

IF DRILL-STEM OR OTHER SPECIAL TESTS ON EXHAUSTION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO. No drill stem tests taken. Maximum deviation: 1 1/2 deg. at 3582 by TOTCO.

ROTARY TOOLS WERE USED FROM 0 FEET TO 1065 FEET, AND FROM FEET TO FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM FEET TO FEET.

PUT TO PRODUCE 7-23-57 13

Oil Well: The production during the first 24 hours was 100 barrels of liquid of which 59

WAS ON = AS WAS EMULSION; I = WATER AND

SEDIMENT, A.P.I. GRAVITY

Q&A WELL. THE PRODUCTION DURING THE FIRST 24 HOURS WAS _____

TANKS OF LIQUID HYDROCARBON. SHUT IN PLUGS - 100

LENGTH OF NAME after 100

PLEASE INDICATE BELOW FORMATION TOPS (in Conformance With Geographical Section of Manual)

1. ARMY	1670	1. DEVONIAN	1. OLD MANO
2. BAIT	1670	2. SKURIAN	2. BLUELAND-BRIULAND
3. BAIT		3. MONTOYA	3. BARRINGTON
4. YATES	2840	4. SIMPSON	4. PICTURED CLIFFS
5. P. RIVER	3077	5. ANKEE	5. ALGERIE
6. QUEEN	3691	6. EISENBERGER	6. MOUNT LOOKOUT
7. GRAYBURG	3960	7. GR. WASH	7. MAYNOD
8. SAN ANDRES		8. GRANITE	8. SASKOTA
9. GLOBETEA		9.	9. ALABRISON
10. DRINKARD		10.	10. PENIM
11. TUBEE		11.	
12. ABO		12.	
13. PENIM		13.	
14. AUSS		14.	

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	1570	1570	Redbeds & shale				
1570	2840	1270	Anhydrite, salt & shale				
2840	3077	237	Sandstone & shale				
3077	3691	614	Dolomite & shale				
3691	3960	269	Sandstone, dolomite & shale				
3960	4065	105	Dolomite				

ATTENTION: STATIONARY EQUIPMENT AND AUTOMATIC EQUIPMENT

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION CONTAINED HEREIN IS A COMPLETE AND CORRECT STATEMENT OF THE FACTS AND ALL INFORMATION CONTAINED HEREIN IS TRUE TO THE BEST OF MY KNOWLEDGE AND BELIEF. I AM A VETERAN OF THE UNITED STATES ARMY.

August 20 1957

COMPANY OR OPERATOR: Atlantic Oil & Refining Company ADDRESS: P. O. Box 2347, Hobbs, New Mexico

[illegible]