NEW EXICO OIL CONSERVATION COM-USSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of		
	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		
Hobbs W M		
Hobbs, N.M.	Place July 13, 1936	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen:		
Continental Oil Co.	as described below at the State A-17	
Company or Operator Lease	e A-17 Well NJ 1 in SE/4	
f Sec. 17 , T. 19-S , R. 37-E	, N. M. P. M., Monument	_Fi
Lea County.		
	RODOGED DI AN ORIGINA	
FOLLOW INSTRUCTIONS IN THE RU	ROPOSED PLAN OF WORK	
FOLLOW INSTRUCTIONS IN THE RU	LES AND REGULATIONS OF THE COMMISSION	
n July 12, 1936 5½" OD casing wa	ROPOSED PLAN OF WORK LES AND REGULATIONS OF THE COMMISSION S set at 3869 and cemented with	
n July 12, 1936 5% OD casing was sacks cement.	es and regulations of the commission as set at 3869° and cemented with	
TOLLOW INSTRUCTIONS IN THE RU In July 12, 1936 $5\frac{1}{5}$ " OD casing wa So sacks cement. Ily 15, after cement has been al	es and regulations of the commission as set at 3869' and cemented with	
n July 12, 1936 5½" OD casing was 50 sacks cement. 1ly 15, after cement has been al ill be tested with 1200# pressur	es and regulations of the commission as set at 3869' and cemented with	
TOLLOW INSTRUCTIONS IN THE RU In July 12, 1936 $5\frac{1}{5}$ " OD casing wa So sacks cement. Ily 15, after cement has been al	es and regulations of the commission as set at 3869° and cemented with	
n July 12, 1936 5½" OD casing was 50 sacks cement. 1ly 15, after cement has been al ill be tested with 1200# pressur	es and regulations of the commission as set at 3869' and cemented with	
n July 12, 1936 5½" OD casing was 50 sacks cement. 1ly 15, after cement has been al ill be tested with 1200# pressur	es and regulations of the commission as set at 3869' and cemented with	
n July 12, 1936 5½" OD casing was 50 sacks cement. 1ly 15, after cement has been al ill be tested with 1200# pressur	es and regulations of the commission as set at 3869' and cemented with	
n July 12, 1936 5½" OD casing was 50 sacks cement. 1ly 15, after cement has been al ill be tested with 1200# pressur	es and regulations of the commission as set at 3869' and cemented with	
n July 12, 1936 5½" OD casing was 50 sacks cement. 1ly 15, after cement has been al ill be tested with 1200# pressur	es and regulations of the commission as set at 3869' and cemented with	
n July 12, 1936 5½" OD casing was 50 sacks cement. 1ly 15, after cement has been al ill be tested with 1200# pressur	es and regulations of the commission as set at 3869' and cemented with	
n July 12, 1936 5½ " OD casing was 50 sacks cement. uly 15, after cement has been al ill be tested with 1200# pressuring.	es set at 3869° and cemented with lowed to set 72 hours casing to both before and after drilling	
n July 12, 1936 5% OD casing was 50 sacks cement. 1ly 15, after cement has been al ill be tested with 1200# pressuring.	es and regulations of the commission as set at 3869' and cemented with	
n July 12, 1936 5½ " OD casing was 50 sacks cement. uly 15, after cement has been al ill be tested with 1200# pressuring.	s set at 3869' and cemented with lowed to set 72 hours casing e both before and after drilling	
n July 12, 1936 5½ " OD casing was 50 sacks cement. uly 15, after cement has been al ill be tested with 1200# pressuring.	continental Oil Company Continental Oil Company Company or Operator By District Supt.	
n July 12, 1936 5½ " OD casing was 50 sacks cement. uly 15, after cement has been al ill be tested with 1200# pressuring.	LES AND REGULATIONS OF THE COMMISSION as set at 3869° and cemented with lowed to set 72 hours casing be both before and after drilling Continental Oil Company Company or Operator By	
n July 12, 1936 5½ " OD casing was 50 sacks cement. uly 15, after cement has been al ill be tested with 1200# pressuring.	continental Oil Company Continental Oil Company Company or Operator By District Supt.	

CR