NEW MEXICO OIL CONSERVATION COMMISSION

This form is <u>not</u> to be used for reporting packer leakage tests in Northwest New Mexi SOUTHEAST NEW MEXICO PACKER LEAKAGE TEST Operator Lease Gulf Oil Corporation Graham State (NCT-G) No. Unit o Location Twp Sec County 17 19 37 of Well Type of Prod Method of Prod Prod. Medium Choke Size Name of Reservoir or Pool (Oil or Gas) Flow, Art Lift (Tbg or Csg) Upper Eumont Plow Gas Cag. ComplLower Monument 011 Pump Tog. 2" W.C. ComplFLOW TEST NO. 1 8:30 A.M. 7-13-70 Both zones shut-in at (hour, date):__ Upper Lower 8:30 A.M. 7-14-70 Well opened at (hour, date):____ Completion Completion Indicate by (X) the zone producing...... X Pressure at beginning of test..... 493 176 Stabilized? (Yes or No)..... Yes Yes Maximum pressure during test..... 493 176 Minimum pressure during test..... 493 37 Pressure at conclusion of test..... 493 37 Pressure change during test (Maximum minus Minimum)...... 0 -139 Was pressure change an increase or a decrease?.......... decr. Total Time On 8:30 A.M. 7-15-70 24 hrs. Well closed at (hour, date):___ Production Oil Production Gas Production bbls; Grav. 31.2 15.0 2143 During Test:_ i; During Test MCF; GOR Remarks FLOW TEST NO. 2 Upper Lower Well opened at (hour, date):____ 8:30 A.M. 7-16-70 _Completion Completion Indicate by (X) the zone producing...... X Pressure at beginning of test..... 493 205 Stabilized? (Yes or No)..... Yes Yes Maximum pressure during test..... 493 205 Minimum pressure during test..... 438 122 Pressure at conclusion of test..... 438 122 Pressure change during test (Maximum minus Minimum)...... **-55** -83 las pressure change an increase or a decrease?......... decr. decr. Total time on 8:30 A.M. 7-17-70 24 hrs. Well closed at (hour, date)____ Production)il Production 0 Gas Production 516.0 _bbls; Grav._ ouring Test: _;During Test MCF: GOR le**mar**ks hereby certify that the information herein contained is true and complete to the best of my nowledge. Gulf Oil Corporation Operator pproved original signed by Ray Iles New Mexico Oil Conser Commission Вy Well Tester Title July 17, 1970

Date

SOUTHEAST NEW MEXICO PACKER LEAKAG ST INSTRUCTIONS

- 1. A packer leakage test shall be commenced—4ch multiply completed well within seven days after actual completion of the well, and animally thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Commission.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Commission in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized and for a minimum of two hours thereafter, provided however, that they need not remain shut-in more than 24 hours.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued until the flowing wellhead pressure has become stabilized and for a minimum of two hours thereafter, provided however, that the flow test need not continue for more than 24 hours.

- 5. Following comp' on of Flow Test No. 1, the well shall again be shutin, in accordance Paragraph 3 above.
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the previously shut-in zone is produced.
- 7. All pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges, the accuracy of which must be checked with a deadweight tester at least twice, once at the beginning and once at the end, of each flow test.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the appropriate District Office of the New Mexico Oil Conservation Commission on Southeast New Mexico Packer Leakage Test Form Revised 11-1-58, together with the original pressure recording gauge charts with all the deadweight pressures which were taken indicated thereon. In lieu of filing the aforesaid charts, the operator may construct a pressure versus time curve for each zone of each test, indicating thereon all pressure changes which may be reflected by the gauge charts as well as all deadweight pressure readings which were taken. If the pressure curve is submitted, the original chart must be permanently filed in the operator's office. Form C-116 shall also accompany the Packer Leakage Test Form when the test period coincides with a gas-oil ratio test period.

• • • • • • • • • • • • • • • • • • •	