

V MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

RECEIVED
MAY 18 1937

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	7*	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Hobbs, New Mexico May 12th 1937.
Place Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Gulf Oil Corp - Gypsy Divison F. W. Kutter "C" Well No. #1 in the _____
Company or Operator Lease

NE/4 of Sec. 18, T. 19, R. 37, N. M. P. M.,
Monument Field, Lea County.

The dates of this work were as follows: Cemented May 9th 19th Tested May 11th 1937.

Notice of intention to do the work was [~~was not~~] submitted on Form C-102 on May 10th 19 37
and approval of the proposed plan was [~~was not~~] obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED


The hole was washed down the casing tested with 1200# pressure applied for 30 mins., the plug drilled and the hole tested with 1200# pressure applied for 30 mins., both tests were OK and after approval of Mr Shepard State oil and gas inspectors, preparations were made to drill ahead.

DUPLICATE

Witnessed by <u>C. L. Hoppe</u> <u>Tom McChesney</u> Name	Gulf <u>Loffland Bros</u> Company	Foreman. <u>Tool pusher.</u> Title
---	---	--

Subscribed and sworn before me this _____

15th day of May, 19 37


Notary Public

My commission expires Feb 8 1941.

I hereby swear or affirm that the information given above is true and correct.

Name C. C. Cummings


Position District Supt.

Representing Gulf Oil Corp - Gypsy Divn.
Company or Operator

Address Hobbs, New Mexico.

Remarks:

162.


Inspector Name
Oil Conservation C'm's'n.
HOBBES, NEW MEX.
Title

MAY 18 1937

THE NATIONAL BUREAU OF STANDARDS

WASHINGTON, D. C. 20540

STANDARD SPECIFICATION FOR THE

TESTING OF STEEL RIVETS AND BOLTS. This specification covers the requirements for the testing of steel rivets and bolts. It includes the methods for determining the tensile strength, shear strength, and elongation of these fasteners. The specification is intended for use by manufacturers, engineers, and inspectors to ensure the quality and reliability of steel fasteners used in construction and industrial applications.

1. Scope and Application

1.1 This specification applies to steel rivets and bolts of all grades and sizes, including those used in structural steelwork, machinery, and other applications. It covers the requirements for the material, manufacturing process, and testing procedures.

1.2 The specification is intended for use by manufacturers, engineers, and inspectors to ensure the quality and reliability of steel fasteners used in construction and industrial applications.

1.3 The specification is based on the latest available data and is subject to revision as new information becomes available.

2. References

2.1 The following references are incorporated by reference into this specification:

- ASTM A307 - Standard Specification for Carbon Steel Bolts and Nuts, 30,000 PSI Tensile Strength
- ASTM A325 - Standard Specification for High-Strength Bolts, 30,000 PSI Tensile Strength
- ASTM A490 - Standard Specification for High-Strength Bolts, 40,000 PSI Tensile Strength

3. Materials and Manufacturing

3.1 The materials used in the manufacture of steel rivets and bolts shall conform to the requirements of the referenced ASTM specifications.

3.2 The manufacturing process shall be controlled to ensure the quality and reliability of the fasteners. This includes the selection of materials, the design of the fastener, and the control of the manufacturing process.

3.3 The fasteners shall be tested to determine their tensile strength, shear strength, and elongation. The test results shall be used to verify that the fasteners meet the requirements of the specification.

3.4 The fasteners shall be marked with the manufacturer's name, the grade of the material, and the size of the fastener. This marking shall be legible and permanent.

3.5 The fasteners shall be stored and handled in a manner that prevents damage and ensures their quality and reliability.

4. Testing and Inspection

4.1 The fasteners shall be tested to determine their tensile strength, shear strength, and elongation. The test results shall be used to verify that the fasteners meet the requirements of the specification.

4.2 The fasteners shall be inspected to ensure that they meet the requirements of the specification. This includes the inspection of the material, the manufacturing process, and the test results.

4.3 The fasteners shall be tested to determine their tensile strength, shear strength, and elongation. The test results shall be used to verify that the fasteners meet the requirements of the specification.

4.4 The fasteners shall be inspected to ensure that they meet the requirements of the specification. This includes the inspection of the material, the manufacturing process, and the test results.

4.5 The fasteners shall be tested to determine their tensile strength, shear strength, and elongation. The test results shall be used to verify that the fasteners meet the requirements of the specification.

4.6 The fasteners shall be inspected to ensure that they meet the requirements of the specification. This includes the inspection of the material, the manufacturing process, and the test results.

4.7 The fasteners shall be tested to determine their tensile strength, shear strength, and elongation. The test results shall be used to verify that the fasteners meet the requirements of the specification.

4.8 The fasteners shall be inspected to ensure that they meet the requirements of the specification. This includes the inspection of the material, the manufacturing process, and the test results.