1. oil

well

below.)
AT SURFACE:

2. NAME OF OPERATOR Texaco Inc.

AT TOTAL DEPTH:

REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE

PULL OR ALTER CASING

MULTIPLE COMPLETE CHANGE ZONES
ABANDON*
(other) Of: Saud

REPAIR WELL

3. ADDRESS OF OPERATOR

UNITED STATE	S
DEPARTMENT OF THE	INTERIOR
GEOLOGICAL SUR	VEY
NOTICES AND REP	ORTS O

(Do not use this form for proposals to drill or to deepen or plug back to a different

other

P. O. Box 728, Hobbs, New Mexico 88240

AT TOP PROD. INTERVAL: (Unit Letter '0')

4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.

reservoir. Use Form 9-331-C for such proposals.)

gas

ୁମ୍ଭିୟୁ ୟEASE
LC-034075
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
· · · · · · · · · · · · · · · · · · ·
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME C. J. Saunders Ledleral
9. WELL NO.
10. FIELD OR WILDCAT NAME
Eunice-Monument Grayburg San Andres
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 18, T-19-S, R-37-E
12. COUNTY OR PARISH 13. STATE
Lea New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3710' (DF)

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rigged up. Pull rods and pump. Install BOP. Pull Tubing.

660' FSL & 1980' FEL

SUBSEQUENT REPORT OF:

X.

- 2. Clean out to 3985'.
- 3. Set cement retainer @ 3937'.

Squeeze &

- 4. Cement w/10,000 gals. injectrol-G & follow w/50 sx. Class 'H' cement containing 2% CaCl. WOC. DOC.
- 5. Set pkr. @ 3692'. Acidize open-hole 3825'-3935' w/3000 gals. 20% NEFE Acid in 3-stages using scale inhibitor. Flush w/70 Bbls. fresh water.
- 6. Install pumping equipment. On 24 Hr potential test ending 4-13-82, well pumped 361 BO, 44 BW & GOR222.

Subsurface Safety Valve: Manu. and Type		Set @	Ft.
18. I hereby certify that the foregoing is true and correct			
SIGNED TITLE ASST. DIST. SUPT. DATE	4-15-8	32	
ACCEPTED FOR RECORD APPROVED BY PETER W. CHESTER TITLE DATE: DATE:	TE	•	
MAY 3 1982			
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO ** Instructions on Reverse Side**			

RECEIVED

MAY 4 1992

MAY 4 1997

O.C.D.
HOBBS GRACE