

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.

Santa Fe, NM 87505

WELL API NO.

30-025-05644

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Amerada Hess Corporation

3. Address of Operator

P.O. BOX 840 SEMINOLE, TX 79360

7. Lease Name or Unit Agreement Name

NORTH MONUMENT G/SA UNIT

BLK 5

8. Well No.

7

9. Pool name or Wildcat

EUNICE MONUMENT G/SA

4. Well Location

Unit Letter G 1980 Feet From The NORTH Line and 1980 Feet From The EAST Line

Section 19 Township 19S Range 37E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-4 THRU 1-22-98

MIRU TYLER WELL SVC. & TOH W/RODS & PUMP. REMOVED WELLHEAD, INSTALLED BOP & TOH W/TBG. RAN 4-3/4" BIT & TAGGED BOTTOM AT 3914' FOR 74' OF FILL. TIH W/5-1/2" LOC-SET RBP & SET AT 3737'. STAR TOOL CIRC. 5-1/2" CSG. CLEAN. SPOTTED 1 SK. SAND ON TOP RBP & ATTEMPTED TO PRESS. TEST CSG. W/NO SUCCESS. WELLHEAD LEAKING. REMOVED BOP & OLD WELLHEAD. INSTALLED NEW WELLHEAD. REINSTALLED BOP & PRESS. TESTED CSG. TO 500 PSI. HELD OK. RAN RETRIEVING HEAD, CIRC. SAND OFF BP, LATCHED ONTO & TOH W/RBP. RAN 4-3/4" BIT & CLEANED OUT OH TO 3995'. WESTERN ATLAS RAN GR/CNL LOG. HALLIBURTON SPOTTED 25 SKS. CLASS H CEMENT FR. 3995' - 3845'. WOC. TIH W/TBG. & TAGGED PBD AT 3920'. SWABBED WELL. AMERICAN FRACMASTER ACIDIZED OH FR. 3762' - 3920' W/4000 GAL. 16% NEFE ACID. SWABBED WELL.

CONTINUED OVER

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Colleen Robinson

TITLE Staff Assistant

DATE 1-26-98

TYPE OR PRINT NAME Colleen Robinson

TELEPHONE NO. 915 758-6700

(This space for State Use)

ORIGINAL SIGNED BY CHRIS WILLIAMS
DISTRICT I SUPERVISOR

FEB 04 1998

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

RAN 4-3/4" BIT & DRLD. CEMENT FR. 3920' - 3950'. CIRC. CLEAN. HALLIBURTON SVC. BROKE CIRC. & PUMPED 14 SKS. CLASS H CEMENT FR. 3950' - 3813'. WOC. TIH & TAGGED PBD AT 3913'. SWABBED WELL. SPOTTED 19 SKS. CLASS H CEMENT FR. 3913' - 3731'. WOC. TIH W/TBG. TO 3913'. HALLIBURTON SVC. SPOTTED 3 SKS. OYSTER SHELLS AT 3913' & BROKE CIRC. REVERSED OUT EXCESS OYSTER SHELLS. SPOTTED 10 SKS. CLASS H CEMENT FR. 3913' - 3827'. WOC. TIH & TAGGED PBD AT 3884'. STAR TOOL LOADED CSG. W/FRESH WATER & ATTEMPTED TO PUMP INTO OH FR. 3884' - 3762'. UNABLE TO GET ANY RATE AT 500 PSI. RAN 4-3/4" BIT, TAGGED CEMENT AT 3884' & DRLD. CEMENT FR. 3884' - 3900'. CIRC. CLEAN. SWABBED WELL. TOH W/BIT. RAN 2-7/8" SN, & 2-7/8" X 5-1/2" TAC ON 2-7/8" TBG. SET SN AT 3891' & TAC AT 3731' W/20,000 PSI TENSION. RAN PUMP & RODS. RDPU & CLEANED LOCATION. 1-22-97: Set pumping unit & motor. Connected electrical service & resumed producing well.

Received
Hobbs
000
1-22-97 10:10:18