

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
		5. State Oil & Gas Lease No. <b>A-1543-1</b>
6. Name of Operator <b>GULF OIL CORPORATION</b>		7. Unit Agreement Name
7. Address of Operator <b>P. O. Box 670, Hobbs, New Mexico 88240</b>		8. Farm or Lease Name <b>Graham State (NCT-D)</b>
8. Location of Well UNIT LETTER <b>P</b> <b>660</b> FEET FROM THE <b>South</b> LINE AND <b>660</b> FEET FROM THE <b>East</b> LINE, SECTION <b>19</b> TOWNSHIP <b>19-S</b> RANGE <b>37-E</b> N.M.P.M.		9. Well No. <b>2</b>
		10. Field and Pool, or Wildcat <b>Eunice - Monument</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3666' GL</b>		12. County <b>Lea</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
 TEMPORARILY ABANDON ☐  
 PULL OR ALTER CASING ☐  
 OTHER **P & A** ☐

PLUG AND ABANDON ☒  
 CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
 COMMENCE DRILLING OPNS. ☐  
 CASING TEST AND CEMENT JOB ☐  
 OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spot cement plug from 3865' to 3700'. Wait on cement. Add cement to bring cement top to 3713'. Spot abandonment mud from cement plug @ 3713' to casing part @ approximately 2159'. Spot 100' cement plug on top of Yates formation. Displace hole with abandonment mud. If necessary, run & set CIBP @ 1600'. Spot cement plug from 1600' to 1500' across top of salt section. Wait on cement. Tag up & add cement to bring top of plug to 1500'. Load hole with abandonment mud from 1500' to 50'. Cap upper 50' with 10 sacks of cement. Install dry hole marker. Clear and clean location.

THE COMPLETION REPORT IS DUE 30 DAYS AFTER THE DATE OF PLACING OPERATIONS FOR THE C-103 TO BE ATTACHED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *M B Sexton Jr.* TITLE Area Engineer DATE 02-01-79

Orig Signed by  
Jerry Sexton

APPROVED BY Jerry Sexton TITLE  DATE FEB 2 1979

CONDITIONS OF APPROVAL, IF ANY

RECEIVED

FEB 1 1979

OIL CONSERVATION COMM.  
EDMUNDS, N. M.