

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

THE TEXAS COMPANY

DRAWER K WINK, TEXAS

STATE "G"

Company or Operator

Address

Well No. 1

in SW 1/4

of Sec. 19

T. 19S

R. 37-E

N. M. P. M. MONUMENT

Field, LEA

County.

Well is 660 feet north of the North line and 660 feet east of the East line of SECTION 19

If State land the oil and gas lease is No. B-2052 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is THE TEXAS COMPANY Address BOX 2338 HOUSTON, TEXAS

Drilling commenced JANUARY 5, 1936 Drilling was completed April 9, 1936

Name of drilling contractor WARREN L. TODD INC. Address DALLAS, TEXAS

Elevation above sea level at top of casing 3660 feet

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3950' to 3980' No. 4, from to
No. 2, from (MAIN) 3920' to 3980' No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

MAIN GAS ZONES

Include data on rate of water inflow and elevation to which water rose in hole. No. 1, from 3400' to 3610'

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13"OD	50	8	Lapweld	233'	Texas	Pattern		
9 5/8"OD	40	8	API	1510'	Baker	Cement Guide Shoe		
7"OD	24	10	API	3832'	Baker	Cement Guide Shoe		

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	13"OD	252'	250	HALLIBURTON		
9	5/8"OD	1327'	800	"		
	7"OD	3850'	400	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3980 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing on test April 10, 1936
The production of the first 24 hours was 38 hrs 146 bbls PL oil per hr. with gas oil ratio of 717%
emulsion; % water; and % sediment. Gravity, Be. 31.3
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

R. B. Brown, Driller Hugh Saunders, Driller
John Grift, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 24th day of Wink, Texas
Name Date

FORMATION RECORD

FORM 0-100

FROM	TO	THICKNESS IN FEET	FORMATION																		
0'	60'	60'	Surface soil and caliche																		
60	69	9	Gravel																		
69	662	593	Red Bed and Sand Rock																		
662	685	23	Lime and Red Rock																		
685	828	143	Red bed and shells																		
828	933	105	Red Rock																		
933	998	65	Lime Shells																		
998	1235	237	Red Rock																		
1235	2822	1587	Salt and Anhydrite																		
2822	2835	13	Anhydrite and Lime																		
2835	2938	103	Brown Lime																		
2938	3433	495	Hard Gray Lime																		
3433	3458	25	Sandy Lime																		
3458	3980	522	Lime																		
			TOTAL DEPTH 3980'																		
IMPORTANT WATER SANDS																					
<table border="1"> <thead> <tr> <th>DEPTH</th> <th>THICKNESS</th> <th>FORMATION</th> </tr> </thead> <tbody> <tr> <td>100'</td> <td>10'</td> <td>Gravel</td> </tr> <tr> <td>200'</td> <td>20'</td> <td>Gravel</td> </tr> <tr> <td>300'</td> <td>30'</td> <td>Gravel</td> </tr> <tr> <td>400'</td> <td>40'</td> <td>Gravel</td> </tr> <tr> <td>500'</td> <td>50'</td> <td>Gravel</td> </tr> </tbody> </table>				DEPTH	THICKNESS	FORMATION	100'	10'	Gravel	200'	20'	Gravel	300'	30'	Gravel	400'	40'	Gravel	500'	50'	Gravel
DEPTH	THICKNESS	FORMATION																			
100'	10'	Gravel																			
200'	20'	Gravel																			
300'	30'	Gravel																			
400'	40'	Gravel																			
500'	50'	Gravel																			
CASING RECORD																					
<table border="1"> <thead> <tr> <th>DEPTH</th> <th>THICKNESS</th> <th>FORMATION</th> </tr> </thead> <tbody> <tr> <td>100'</td> <td>10'</td> <td>Gravel</td> </tr> <tr> <td>200'</td> <td>20'</td> <td>Gravel</td> </tr> <tr> <td>300'</td> <td>30'</td> <td>Gravel</td> </tr> <tr> <td>400'</td> <td>40'</td> <td>Gravel</td> </tr> <tr> <td>500'</td> <td>50'</td> <td>Gravel</td> </tr> </tbody> </table>				DEPTH	THICKNESS	FORMATION	100'	10'	Gravel	200'	20'	Gravel	300'	30'	Gravel	400'	40'	Gravel	500'	50'	Gravel
DEPTH	THICKNESS	FORMATION																			
100'	10'	Gravel																			
200'	20'	Gravel																			
300'	30'	Gravel																			
400'	40'	Gravel																			
500'	50'	Gravel																			
MUDLOG AND CORRELATION RECORD																					
<table border="1"> <thead> <tr> <th>DEPTH</th> <th>THICKNESS</th> <th>FORMATION</th> </tr> </thead> <tbody> <tr> <td>100'</td> <td>10'</td> <td>Gravel</td> </tr> <tr> <td>200'</td> <td>20'</td> <td>Gravel</td> </tr> <tr> <td>300'</td> <td>30'</td> <td>Gravel</td> </tr> <tr> <td>400'</td> <td>40'</td> <td>Gravel</td> </tr> <tr> <td>500'</td> <td>50'</td> <td>Gravel</td> </tr> </tbody> </table>				DEPTH	THICKNESS	FORMATION	100'	10'	Gravel	200'	20'	Gravel	300'	30'	Gravel	400'	40'	Gravel	500'	50'	Gravel
DEPTH	THICKNESS	FORMATION																			
100'	10'	Gravel																			
200'	20'	Gravel																			
300'	30'	Gravel																			
400'	40'	Gravel																			
500'	50'	Gravel																			
PLUGS AND ADAPTERS																					
<table border="1"> <thead> <tr> <th>DEPTH</th> <th>THICKNESS</th> <th>FORMATION</th> </tr> </thead> <tbody> <tr> <td>100'</td> <td>10'</td> <td>Gravel</td> </tr> <tr> <td>200'</td> <td>20'</td> <td>Gravel</td> </tr> <tr> <td>300'</td> <td>30'</td> <td>Gravel</td> </tr> <tr> <td>400'</td> <td>40'</td> <td>Gravel</td> </tr> <tr> <td>500'</td> <td>50'</td> <td>Gravel</td> </tr> </tbody> </table>				DEPTH	THICKNESS	FORMATION	100'	10'	Gravel	200'	20'	Gravel	300'	30'	Gravel	400'	40'	Gravel	500'	50'	Gravel
DEPTH	THICKNESS	FORMATION																			
100'	10'	Gravel																			
200'	20'	Gravel																			
300'	30'	Gravel																			
400'	40'	Gravel																			
500'	50'	Gravel																			
RECORD OF SHOOTING OR CHEMICAL TREATMENT																					
<table border="1"> <thead> <tr> <th>DEPTH</th> <th>THICKNESS</th> <th>FORMATION</th> </tr> </thead> <tbody> <tr> <td>100'</td> <td>10'</td> <td>Gravel</td> </tr> <tr> <td>200'</td> <td>20'</td> <td>Gravel</td> </tr> <tr> <td>300'</td> <td>30'</td> <td>Gravel</td> </tr> <tr> <td>400'</td> <td>40'</td> <td>Gravel</td> </tr> <tr> <td>500'</td> <td>50'</td> <td>Gravel</td> </tr> </tbody> </table>				DEPTH	THICKNESS	FORMATION	100'	10'	Gravel	200'	20'	Gravel	300'	30'	Gravel	400'	40'	Gravel	500'	50'	Gravel
DEPTH	THICKNESS	FORMATION																			
100'	10'	Gravel																			
200'	20'	Gravel																			
300'	30'	Gravel																			
400'	40'	Gravel																			
500'	50'	Gravel																			
RECORD OF DRILLING AND SPECIAL TESTS																					
<table border="1"> <thead> <tr> <th>DEPTH</th> <th>THICKNESS</th> <th>FORMATION</th> </tr> </thead> <tbody> <tr> <td>100'</td> <td>10'</td> <td>Gravel</td> </tr> <tr> <td>200'</td> <td>20'</td> <td>Gravel</td> </tr> <tr> <td>300'</td> <td>30'</td> <td>Gravel</td> </tr> <tr> <td>400'</td> <td>40'</td> <td>Gravel</td> </tr> <tr> <td>500'</td> <td>50'</td> <td>Gravel</td> </tr> </tbody> </table>				DEPTH	THICKNESS	FORMATION	100'	10'	Gravel	200'	20'	Gravel	300'	30'	Gravel	400'	40'	Gravel	500'	50'	Gravel
DEPTH	THICKNESS	FORMATION																			
100'	10'	Gravel																			
200'	20'	Gravel																			
300'	30'	Gravel																			
400'	40'	Gravel																			
500'	50'	Gravel																			
TOOLS USED																					
<table border="1"> <thead> <tr> <th>DEPTH</th> <th>THICKNESS</th> <th>FORMATION</th> </tr> </thead> <tbody> <tr> <td>100'</td> <td>10'</td> <td>Gravel</td> </tr> <tr> <td>200'</td> <td>20'</td> <td>Gravel</td> </tr> <tr> <td>300'</td> <td>30'</td> <td>Gravel</td> </tr> <tr> <td>400'</td> <td>40'</td> <td>Gravel</td> </tr> <tr> <td>500'</td> <td>50'</td> <td>Gravel</td> </tr> </tbody> </table>				DEPTH	THICKNESS	FORMATION	100'	10'	Gravel	200'	20'	Gravel	300'	30'	Gravel	400'	40'	Gravel	500'	50'	Gravel
DEPTH	THICKNESS	FORMATION																			
100'	10'	Gravel																			
200'	20'	Gravel																			
300'	30'	Gravel																			
400'	40'	Gravel																			
500'	50'	Gravel																			
PRODUCTION																					
<table border="1"> <thead> <tr> <th>DEPTH</th> <th>THICKNESS</th> <th>FORMATION</th> </tr> </thead> <tbody> <tr> <td>100'</td> <td>10'</td> <td>Gravel</td> </tr> <tr> <td>200'</td> <td>20'</td> <td>Gravel</td> </tr> <tr> <td>300'</td> <td>30'</td> <td>Gravel</td> </tr> <tr> <td>400'</td> <td>40'</td> <td>Gravel</td> </tr> <tr> <td>500'</td> <td>50'</td> <td>Gravel</td> </tr> </tbody> </table>				DEPTH	THICKNESS	FORMATION	100'	10'	Gravel	200'	20'	Gravel	300'	30'	Gravel	400'	40'	Gravel	500'	50'	Gravel
DEPTH	THICKNESS	FORMATION																			
100'	10'	Gravel																			
200'	20'	Gravel																			
300'	30'	Gravel																			
400'	40'	Gravel																			
500'	50'	Gravel																			
EMPLOYEES																					
<table border="1"> <thead> <tr> <th>DEPTH</th> <th>THICKNESS</th> <th>FORMATION</th> </tr> </thead> <tbody> <tr> <td>100'</td> <td>10'</td> <td>Gravel</td> </tr> <tr> <td>200'</td> <td>20'</td> <td>Gravel</td> </tr> <tr> <td>300'</td> <td>30'</td> <td>Gravel</td> </tr> <tr> <td>400'</td> <td>40'</td> <td>Gravel</td> </tr> <tr> <td>500'</td> <td>50'</td> <td>Gravel</td> </tr> </tbody> </table>				DEPTH	THICKNESS	FORMATION	100'	10'	Gravel	200'	20'	Gravel	300'	30'	Gravel	400'	40'	Gravel	500'	50'	Gravel
DEPTH	THICKNESS	FORMATION																			
100'	10'	Gravel																			
200'	20'	Gravel																			
300'	30'	Gravel																			
400'	40'	Gravel																			
500'	50'	Gravel																			