

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to: Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

The Texas Company

State "G"

State "G" Company or Operator Well No. 2 in SW 1/4 of Sec. 19 T. 10-S

R. 37-E N. M. P. M. Monument Field, Lea County.

Well is 4620 feet south of the North line and 4620 feet west of the East line of Section 19

If State land the oil and gas lease is No. B-2052 Assignment No. _____

If patented land the owner is _____ Address _____

If Government land the permittee is _____ Address _____

The Lessee is The Texas Company Address Box 2552 Houston, Texas

Drilling commenced February 5 19 36 Drilling was completed March 20 19 36

Name of drilling contractor Gardner Bros. Address Dallas, Texas

Elevation above sea level at top of casing 3678 feet.

The information given is to be kept confidential until _____ 19 _____

OIL SANDS OR ZONES

No. 1, from 3680 to 4004' No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.

No. 2, from _____ to _____ feet.

No. 2, from _____ to _____ feet.

No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
<u>15 1/2</u>	<u>70#</u>	<u>8</u>	<u>Lweld</u>	<u>240'</u>	<u>Texas Pattern</u>			
<u>9 5/8" OD</u>	<u>40#</u>	<u>8 API</u>	<u>Smless.</u>	<u>1324'</u>	<u>Baker Cement Guide</u>			
<u>7" OD</u>	<u>24#</u>	<u>10 API</u>	<u>Smless.</u>	<u>3853'</u>	<u>Baker Cement Guide</u>			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	<u>15 1/2</u>	<u>258'</u>	<u>250</u>	<u>Halliburton</u>		
	<u>9 5/8 OD</u>	<u>1341'</u>	<u>800</u>	<u>"</u>		
	<u>7" OD</u>	<u>3870'</u>	<u>400</u>	<u>"</u>		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____

Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 4004 feet, and from _____ feet to _____ feet

Cable tools were used from 0 feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing On Test March 23 19 36

The production of the first 24 hours was On 2 Hr Test Flowed 162 Bbls. Per Hour barrels of fluid of which 100 % was oil; _____ %

emulsion; _____ % water; and _____ % sediment. Gravity, Be. 31.9

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

T.W. Clark Driller W. N. Hawks Driller

C. White Driller _____ Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given hereon is a complete and correct record of the well and all

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0'	35	35	Caliche
35	65	30	Sand
65	930	865	Shale & Shells
930	1259	329	Red Rock
1259	1375	116	Anhydrite
1375	2655	1280	Anhydrite and salt
2655	2667	12	Lime
2667	2765	98	Anhydrite and lime
2765	2827	62	Gray lime and Anhy.
2827	2868	41	Potash and lime
2868	2899	31	Gray lime
2899	3261	362	Lime and Anhy.
3261	3287	26	Sandy lime
3287	3302	15	Broken brown lime
3302	3410	108	Hard gray lime
3410	3560	150	Brown lime
3560	3585	25	White lime
3585	3758	173	Broken Sandy lime
3758	3835	77	Brown lime
3835	3870	35	Broken sand and lime
3870	3891	21	Broken lime
3891	4004	113	Porous lime
			Total Depth 4004 feet.