NE MEXICO OIL CONSERVATION COMPSSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X	NOTICE OF INTENTION TO SHOOT OR		
North On Difference and Divide Dr. and		CHEMICALLY TREAT WELL NOTICE OF INTENTION TO PULL OR		
NOTICE OF INTENTION TO CHANGE PLANS		OTHERWISE ALTER CASING		
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL		
NOTICE OF INTENTION TO DEEPEN WELL				
Monument, New	Mexic			
		Place Date		
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.				
Gentlemen:				
Following is a notice of intention to do certain work	as des	ribed below at the		
Amerada Petroleum Corporation Sta	ate"L"	Well No. 1 in SW1 NW1		
Company or Operator Lease	е			
	······	N. M. P. M., Monument Field		
County.				
9-5/8" 35# 8-thd. New Seamless casing by the Halliburton method with 500 s	ng was sacks by app	ly ing 1200# pump pressure and allowing		
9-5/8" 35# 8-thd. New Seamless casin by the Halliburton method with 500 s Casing and fittings will be tested b to stand undisturbed for thirty minu casing and the same test again appli	ng was sacks by app	set in this well at 2470 and cemented cement.		
9-5/8" 35# 8-thd. New Seamless casin by the Halliburton method with 500 s Casing and fittings will be tested b to stand undisturbed for thirty minu	ng was sacks by app	set in this well at 2470° and cemented cement. ly ing 1200# pump pressure and allowing Cement plug will then be drilled out of		
9-5/8" 35# 8-thd. New Seamless casing by the Halliburton method with 500 stains and fittings will be tested by to stand undisturbed for thirty minutesing and the same test again appliminutes.	ng was sacks by app	set in this well at 2470° and cemented cement. ly ing 1200# pump pressure and allowing Cement plug will then be drilled out of		
9-5/8" 35# 8-thd. New Seamless casing by the Halliburton method with 500 s Casing and fittings will be tested by to stand undisturbed for thirty minuscasing and the same test again appliminutes. Approved	ng was lacks by app ltes.	set in this well at 2470' and cemented cement. ly ing 1200# pump pressure and allowing Cement plug will then be drilled out of allowed to stand undisturbed for thirty Amerada Petroleum Corporation Company or Operator		
9-5/8" 35# 8-thd. New Seamless casing by the Halliburton method with 500 s Casing and fittings will be tested by to stand undisturbed for thirty minuscasing and the same test again appliminutes. Approved	ng was lacks by app ltes.	set in this well at 2470' and cemented cement. ly ing 1200# pump pressure and allowing Cement plug will then be drilled out of allowed to stand undisturbed for thirty Amerada Petroleum Corporation Company or Operator By Janky Position Farm Boss		

110

on the state of the section of the s

BETTER BOUNDERS MICHES

Section 1985 Section 1986 Section 1986		Bernard County Said (Grand) Constant County County (Grand)			Transfer of the state of the st
		. Marin 2011 grade the second of the	ACCOMPANIES OF THE		
		e de la companya de La companya de la companya de l	The second secon		ener i de la companya de la company La companya de la co
		1			
					ty ext
	•				
			ا ما الله الله الله الله الله الله الله		
	The Oracle Miles of the Service of t	E. W. C. W. C. L. C. C. Code: Whiteholder, Color, Co. C.			1 p 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
	:				
•					
				. *	
•		* 500			
					· -
		• .			
			•		
					• *
					•
		and the second second			
		The terms of			
			e - 2.21		
	i i				