

COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name State "T"
9. Well No. 5
10. Field and Pool, or Wildcat Eumont Queen
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>
2. Name of Operator Amerada Hess Corporation
3. Address of Operator Drawer D, Monument, NM 88265
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>20</u> TOWNSHIP <u>19 S</u> RANGE <u>37 E</u> NMPM.

15. Elevation (Show whether DF, RT, GR, etc.) 3680' DF

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to pull 1½" and 3½" tbg and set retrievable bridge plug in 6-5/8" csg at approximately 3690' and dump 3 sks sand on top of bridge plug. Test w/1500#. Set pkr at 3400' and squeeze Eumont Queen Zone 6-5/8" csg perfs from 3508' to 3600' and from 3618' to 3646' w/250 sks class "C" cement mixed w/2% CaCl and 1% FLA. Drill out cement and test the squeeze. Retrieve bridge plug.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E.B. Fisher TITLE Supv. Admin. Serv. DATE November 1, 1977
APPROVED BY John Kenyon TITLE Geologist DATE Nov 1 1977
CONDITIONS OF APPROVAL, IF ANY: