

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B1431

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name State "T" Bty. 3
3. Address of Operator Drawer D, Monument, New Mexico 88265	9. Well No. 6
4. Location of Well UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM East LINE, SECTION 20 TOWNSHIP 19S RANGE 37E N.M.P.M.	10. Field and Pool, or Wildcat Eunice Monument G/SA
15. Elevation (Show whether DF, RT, CR, etc.) 3683' DF	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe the Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

September 7 to September 11, 1980- Pulled rods & pump. Checked fill in open hole at 3980' & pulled tbq. Cleaned out fill in open hole fr. 3980' to 3984' w/3-1/2" sand pump. String shot Grayburg San Andres zone in open hole fr. 3984' to 3990' w/300 gpf. Cleaned out fill in open hole fr. 3984' to 3990' w/3-1/2" sand pump. String shot Grayburg San Andres zone in open hole fr. 3848' to 3990' w/500 gpf. Checked top of fill in open hole at 3985'. Ran pkr. & 2-7/8" tbq. & set pkr. at 3797'. Tested tbq. to 2000#. Held OK. Loaded csg. & pressured to 500#. Acid Engineers acidized Grayburg San Andres zone in open hole fr. 3838' to 3985' w/500 gal. 15% HCl acid, 1000 gal. 30# gel, 4000 gal. 15% gelled retarded HCl acid, flushed w/36 bbls. 10# gel. Swabbed load, re-ran tbq., pump & rods & resumed pumping.

Test of 9-14-80: Pumped 7 b.o. & 37 b.w. in 24 hrs. on 7-33" SPM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>E. J. Fisher</u>	TITLE <u>Supv. Adm. Ser.</u>	DATE <u>9-15-80</u>
APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u></u>
CONDITIONS OF APPROVAL, IF ANY:		