NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the district Drythe Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin district additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below Notice of Intention Notice of Intention to Notice of Intention TO CHANGE PLANS TEMPORARILY ABANDON WELL TO DRILL DEEPER Notice of Intention Notice of Intention Notice of Intention TO PLUG WELL TO PLUG BACK TO SET LINER Notice of Intention Notice of Intention Notice of Intention to Squeeze TO ACIDIZE то Sноот (Nitro) Notice of Intention Notice of Intention NOTICE OF INTENTION TO GUN PERFORATE (OTHER) (OTHER) Dually Complete OIL CONSERVATION COMMISSION Hobbs, New Mexico SANTA FE, NEW MEXICO March 24, 1953 Gentlemen: Following is a Notice of Intention to do certain work as described below at the New Mexico State D Humble Oil & Refining Company (Company or Operator) T 19-S R 37-E NMPM, Morresont 1/4 of Sec (40-acre Subdivision) FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS) Objective: The purpose of this job is to dually complete the well to produce gas and eil from the Grayburg formation through the tubing and gas from the queen formation via the twhine-casing annulus. Intended Precedure: It is proposed to dually complete the well according to the following procedure: (1) move in workover unit and rig up, (2) pull rods and tubing, (3) run radioactivity leg, (4) set Baker Model "DA" production packer at 3725 fecton wire line, (5) rem tubing, test packer for seal, drop standing valve and test, (6) back off Baker safety joint and load hole with salt water, (7) pull tubing, run retrievable junk catcher, and perforate from 3525 to 3700 with two jet shots per foot, (8) fish out junk basket, (9) run straddle packer, wash perferations with 500 gallons of mud acid and test, (10) treat with 5000 gallons of low tension acid and test, (11) kill well and pull straddle packer, (12) rerun tubing with Cames mandrel, (13) swab in and clean up gas some and set Monel dummy valve in Cames Mandrel, (14) pall standing valve, (15) rerun rods and pump or install gas lift equipment and place well on production. Humble Oil & Refining Company Except as follows: District Superintendent Position. Approved Send Communications regarding well to: OIL CONSERVATION COMMISSION Humble Oil & Refining Company Name..

Address.

Box 2347, Hobbs, N. M.