NF XICO OIL CONSERVATION COAT ISION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF IN	TENTION TO TEST CASING S	SHUT-OFF	NOTICE OF CHEMICA	INTENTION TO SHOOT OR ALLY TREAT WELL	x
NOTICE OF IN	TENTION TO CHANGE PLA	NS	NOTICE OF OTHERW	INTENTION TO PULL OR	
OTICE OF IN	TENTION TO BEPAIR WE	LL		INTENTION TO PLUG W ELL	
NOTICE OF IN	ITENTION TO DEEPEN WE	LL			-
					<u> </u>
		Midland,	Place	November 24, 1936	
IL CONSERV	VATION COMMISSION,				
anta Fe, New	Mexico.				
Gentlemen:					
'ollowing is a	notice of intentiton to do	certain work as desc	ribed below at	the	
Remble 01	1 & Refining Compan	y N. M. State	"D"	Well No. 1 in SE/4	of NE/
• •	or Operator	Lease R. 57-E , N	мрм	Monument	774-14
	I.en.				Field,
		County.			
	TATEL TATA	TAILS OF PROP	2000 00 410		
	FOLLOW INSTRUCTION	ONS IN THE RULES AT	ND REGULATION	NS OF THE COMMISSION	
la évené w	mll with 1000 colle	ma of Domell V		20541 to 80041 to 14	
o treat w	ell with 1000 galle	ons of Dowell X	acid from	3956' to 3996' in lime	
cometice.	5-1/2" easing set	ens of Dowell X t at 5750°. New	acid from	3956' to 3996' in lime ing treated in an effor	t
Commetica.	ell with 1000 galls 5-1/2" easing set better promeser.	ens of Dowell X t at 5750°. New	acid from well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X t at 5750°. New	acid from well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X at 3750°. New	acid from well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X t at 3750°. New	acid from well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X at 3750°. New	acid from well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X at 3750°. New	acid from well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X at 3750°. New	acid from well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X at 3750°. New	r well - be	3956' to 3996' in lime ing treated in an effor	t
Commetica.	5-1/2" easing set	ens of Dowell X at 3750°. New	acid from well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X at 5750°. New	r well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X t at 5750°. New	r well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X t at 5750°. New	r well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X t at 5750°. New	r well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X t at 5750°. New	r well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	ens of Dowell X t at 5750°. New	r well - be	3956' to 3996' in lime ing treated in an effor	t
cometice.	5-1/2" easing set	t at 5750°. Ne	r well - be	ing treated in an effor	t
formation.	5-1/2" easing set	ens of Dowell X at 5750°. New	r well - be	ing treated in an effor	t
o make a	5-1/2" easing set	t at 5750°. Ne	r well - be	ing treated in an effor	t
pproved	5-1/2" easing set	t at 5750°. Ne	r well - be	ing treated in an effor	t
o make a	5-1/2" easing set	t at 5750°. Ne	Humble	Oil & Refining Company Company or Operator	t
o make a	5-1/2" easing set	t at 5750°. Ne	Humble By Position	Oil & Refining Company Company or Operator Division Chief Clerk	
Approved	5-1/2" easing set	t at 5750°. Ne	Humble By Position	Oil & Refining Company Company or Operator	
Approved	5-1/2" easing set	t at 5750°. Ne	Humble By Position Send	Oil & Refining Company Company or Operator Division Chief Clerk	
Approved	better producer.	t at 5750°. Ne	Humble By Position Send Name	Oil & Refining Company Company or Operator Division Chief Clerk communications regarding well W. T. Doherty	to
Approved	better protect. DWS:	t at 5750°. Ne	Humble By Position Send Name	Oil & Refining Company Company or Operator Division Chief Clerk communications regarding well	to
Approvedarcept as follows	better protect. DWS:	t at 5750°. Ne	Humble By Position Send Name	Oil & Refining Company Company or Operator Division Chief Clerk communications regarding well W. T. Doherty	to

A STATE OF

$(x_{i+1}, \dots, x_{i+1}, x_{i+1}, \dots, x_{i+1})$

 $\label{eq:continuous} (x,y) = (x,y) + (x,y) + (x,y)$ where (x,y) = (x,y) + (x,y) +

 $\label{eq:continuous} (x,y,y,z) = (x,y,z) + (x,y,z) +$

144.45 A 144

Control Control of the State of the Control of the and the second of the second o

· ·

Color Division of the first to the first enter Constitution (Constitution)

the first of the second of

. . .

and the second of the second o