

Santa Fe, New Mexico

408BS OFFICE OCC

1966 SEP 9 AM 10 59
CORD

WELL RECORD

AREA 640 ACRES
LOCATE WELL CORRECTLY

Texas Crude Oil Company
(Company of Operator)

McNeil
(Lan)

Well No. 1-25, in SW 1/4 of NE 1/4, of Sec. 25, T. 19-S, R. 37-E, NMPM.

Wildcat Pool, **Len** County.

Well is 1980 feet from North line and 1980 feet from East line
of Section 25. If State Land the Oil and Gas Lease No. is _____

Drilling Commenced.....June 14,.....1959..... Drilling was Completed.....July 1,.....1959.....

Name of Drilling Contractor..... **B. L. McFarland, Inc.**.....

Address 3612 West Hall Street, Midland, Texas

Elevation above sea level at Top of Tubing Head.....3610 est. The information given is to be kept confidential until
..... 19.....

OIL SANDS OR ZONES

No. 1, from 4225 to 4235 No. 4, from _____ to _____

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from No fresh water zones encountered feet. _____

No. 2, from.....to.....feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8 ^N	32.0	Used	300	Horse	---	---	Surface
5-1/2 ^N	15.5	New	4304	Horse	---	---4226-40	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8-5/8	300	150	Pump		
7-7/8	5-1/2	1300	350	Pump		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Acidized 500 gals. acid 1226'-40'.

Result of Production Stimulation.....180 bbls. salt water & 1/2 bbl. oil per day.

..Depth Cleaned Out.....

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 1300 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing July 11, 19 59

OIL WELL: The production during the first 24 hours was 214 barrels of liquid of which 1/2 was oil; % was emulsion; 99 1/2 % water; and % was sediment. API Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	1515	T. Devonian	T. Ojo-Alamo
T. Salt	1635	T. Silurian	T. Kirtland-Fruitland
B. Salt	2672	T. Montoya	T. Farmington
T. Yates	2832	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	3092	T. McKee	T. Menefee
T. Queen	3610	T. Ellenburg r.	T. Point Lookout
T. Grayburg	3980	T. Gr. Wash	T. Mancos
T. San Andres	4215	T. Granite	T. Dakota
T. Glorieta		T.	T. Morrison
T. Drinkard		T.	T. Penn.
T. Tubbs		T.	T.
T. Abo		T.	T.
T. Penn.		T.	T.
T. Miss.		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1515	1515	Sand, lime & shale				
1515	1635	90	Anhydrite				
1635	2672	1027	Salt				
2672	2832	160	Anhydrite				
2832	3092	260	Sand & anhydrite				
3092	3610	518	" "				
3610	3980	370	Sand, anhydrite & dolomite				
3980	4215	235	" "				
4215	T.D.	85	Dolomite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

September 4, 1959

(Date)

Company or Operator Texas Crude Oil Company

Address 1201 V & J Tower Bldg., Midland, Texas

Name J. R. Newman

Position Title Petroleum Engineer

OX 5, Pile 1, FW 1, McFarland 1, Atlantic 1, Gulf 1, Ohio 1, Shelly 1.