

District I  
PO Box 1980, Hobbs, NM 88241-1980  
District II  
PO Drawer DD, Artesia, NM 88211-0719  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico  
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION  
PO Box 2088  
Santa Fe, NM 87504-2088

Form C-101  
Revised February 10, 1994  
Instructions on back  
Submit to Appropriate District Office  
State Lease - 6 Copies  
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator Name and Address. Amerada Hess Corporation Drawer D Monument, New Mexico 88265		1 OGRID Number 000495
		1 API Number 30-025-05714
1 Property Code 000135	1 Property Name #1204 North Monument Grayburg San Andres Unit	1 Well No. 288

7 Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D	28	19S	37E		660	North	660	West	Lea

8 Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County

9 Proposed Pool 1 Eunice Monument Grayburg San Andres	10 Proposed Pool 2
--	--------------------

11 Work Type Code E	12 Well Type Code O	13 Cable/Rotary	14 Lease Type Code S	15 Ground Level Elevation 3654'
16 Multiple No	17 Proposed Depth 4007	18 Formation Grayburg San Andres	19 Contractor	20 Spud Date

21 Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
	13-3/8"		34'		
	9-5/8"		1378'		
	7"		3722'		

22 Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

Plan to MIRU pulling unit & air unit. Cut off P & A marker. Install wellhead & BOP. TIH w/tbg., D.C.'s & bit. Drill out surface plug., cement plug & retainer at 2140' & clean out to plug at 3565'. Perform csg. integrity test. Drill out cement plug & CIBP at 3565'. Clean out to TD & deepen 29' to 3908'. TOH w/bit. Acidize well w/5,000 gal. 15% NEFE DI HCL w/3% DP-77MX solvent. Move tool across O.H. fr. 3722' - 3908' throughout acid job. TIH w/pkr. set at + 3650'. Swab well. TIH w/prod. tbg. Remove BOP, install wellhead & TIH w/pump & rods.

CONTINUED OVER

23 I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature:

Printed name:

Title:

Date:

7-31-96

Phone:

505 393-2144

OIL CONSERVATION DIVISION

Approved by:

ORIGINAL SIGNER BY MARY SEXTON

Title:

DISTRICT SUPERVISOR

Approval Date:

AUG 28 1996

Expiration Date:

Conditions of Approval:

Attached ☐

