

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR NOTICES TO ABANDON OR TO REOPEN A WELL BACK TO A DIFFERENT RESERVOIR. USE THAT FORM FOR PERMIT TO REOPEN A WELL FOR A DIFFERENT RESERVOIR.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
Marathon Oil Company

Address of Operator
P. O. Box 2409, Hobbs, New Mexico 88240

Location of Well
UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM
THE East LINE, SECTION 28 TOWNSHIP 19S RANGE 37E MAP.

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
164

7. Unit Agreement Name

8. Name of Lease Name
State A-3071 "D"

9. Well No.
1

10. Field and Pool, or Validity
Eumont Gas

12. County
Lea

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ REMEDIAL WORK ☐ ALTERING CASING ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐ OTHER ☐ CASING TEST AND CEMENT JOB ☐

OTHER ☐

SUBSEQUENT REPORT OF:

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Intend to plug and abandon Well No. 1 using the following procedure:

1. Set permanent bridge plug @ 3850'.
2. Spot 10 sacks (100') of API Class "C" cement on bridge plug.
3. Pull up 3 jts. and displace hole with mud.
4. Set permanent bridge plug @ 2875'.
5. Spot 20 sacks (200') of API Class "C" cement on bridge plug.
6. Set permanent bridge plug @ 2675'.
7. Spot 10 sacks (100') API Class "C" cement on bridge plug. POH with tubing.
8. Set permanent bridge plug @ 260'.
9. POH with tubing. Dump 25 sacks API Class "C" cement to cap hole.
10. Dig out and expose casing to a depth of 4'.
11. Cut off casing 3' from surface and weld on cap.
12. Weld on 7' X 4" post marked according to Statewide Rule 202-B.
13. Pour 3' of concrete around post.
14. Clear and level location.

(Cmt. Circulated on 5 1/2" cgl)

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED William R. Shuck TITLE Production Engineer DATE February 13, 1978

APPROVED BY John Runyan Geologist

CONDITIONS OF APPROVAL, IF ANY:

FEB 14 1978

DATE

RECEIVED

FEB 13 1978

OIL CONSUMPTION CONTROL
HOBBS, N. M.