

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS OF WELLS

RECEIVED
AUG 29 1946
RECEIVED

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	X
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Monument, New Mexico

Place

August 27, 1946

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amarada Petroleum Corporation State K Well No. 2 in the
Company or Operator LeaseNE 1/4 of NW 1/4 of Sec. 29, T. 19S, R. 37E, N. M. P. M.,
Monument Field, Lea County.

The dates of this work were as follows: August 17th to August 20, 1946.

Notice of intention to do the work (was not) submitted on Form C-102 on 19

and approval of the proposed plan (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3960' Total Depth, Rigged up and killed well, to test for Casing Leak, Set Model K Baker Cement Retainer as a bridging plug at 3483' and dumped 2 sac Incon cement on top of it. August 18, 1946 pumped plug down with Halliburton 900# to 1500# pressure and found 2 holes at 1515' and 1557'. August 20, 1946 ripped 2 holes in 6 5/8" Casing at 1600' with Beach Ross Casing Perforator, pumped into casing with 275# Pressure and got circulation thru braden Head, Started cementing at 3PM and got returns thru braden head with 400 Sac cement and closed gate on braden head, and dumped 300 sac more, pumped plug down to 500' no pressure, shut down for 30 Mins and pumped plug to 800' 500# Pressure, down 20 mins, plug to 1000' 1000# Press.

Witnessed by Dan Topper. Amarada Pet. Corp. Asst. Dist. Supt.

Name

Company

Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

27th day of August, 1946

Name Dan Topper

Position Asst. Dist. Supt.

Representing Amarada Pet. Corp.,
Company or Operator

My commission expires

My Commission Expires May 9, 1946

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date

Roy Yankbrough
Oil & Gas Inspector
Title