

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B1384	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation		8. Farm or Lease Name State "P" Gas Comm.
3. Address of Operator Drawer D, Monument, New Mexico 88265		9. Well No. 2
4. Location of Well UNIT LETTER <u>M</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>29</u> TOWNSHIP <u>19-S</u> RANGE <u>37-E</u> NMPM.		10. Field and Pool, or Wildcat Eumont Queen
15. Elevation (Show whether DF, RT, GR, etc.) 3610' DF		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Eumont Queen</u> <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

June 1977:

Pulled rods, pump, tbg. & pkr. Ran retrievable bridge plug & pkr. Set bridge plug in 6-5/8" csg. at 3662'. Tested OK. Spotted 3 sks. sand on top of bridge plug. Set pkr. at 3214' & squeezed Eumont Queen zone thru 6-5/8" csg. perf. fr. 3330' to 3600' w/240 sks. Class C cement w/additives with 106 sks. cement in formation. WOC & drld. out cement fr. 3213' to 3620' & tested squeeze w/1500# press. Held OK. Recovered bridge plug & ran tbg., pump & rods and resumed production from Grayburg San Andres.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>C.B. Fisher</u>	TITLE <u>Supv. Adm. Ser.</u>	DATE <u>6-17-77</u>
C.B. Signed by		
APPROVED BY	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

JUN 25 1977

CL. CONGRESSIONAL COMM.
WESB, D. M.