

NEW MEXICO OIL CONSERVATION COMMISSION

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-1533-122	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL, RE-DRILL, RE-ENTER OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT TO DRILL" (C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name State "0"
3. Address of Operator Drawer "D", Monument, New Mexico 88265	9. Well No. 1 2
4. Location of Well UNIT LETTER G 660 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 30 TOWNSHIP 19-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat Eunice-Monument (G-SA)
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pulled production equipment. Set 6-5/8" cast iron bridge plug at 3835', with sand on top. Acidized perfs. 3794' to 3826' with 1500 gals. 15% NE acid. Swab tested. Perf. 6-5/8" csg. with 2 shots at: 3721', 3728', 3736', 3743', 3747', 3749', 3753', 3759', 3761', 3765', 3768'. Total of 22 shots. Set ret. bridge plug at 3780'. Acidized perfs. 3721' to 3768' w/3000 gals. 15% NE acid. with ball sealers. Swab tested. Non-productive. Closed all valves & T.A. pending further evaluation.

Expires 11/1/76

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>M. Black</u>	TITLE <u>Supver., Admin. Services</u>	DATE <u>10-21-75</u>
APPROVED BY <u>Jerry Sexton</u>	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		