NEW LXICO OIL CONSERVATION COM SSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of	
OTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
OTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
OTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
OTICE OF INTENTION TO DEEPEN WELL	
Monument, New	Mexico May 12, 1936 Place Date
IL CONSERVATION COMMISSION, anta Fe, New Mexico.	
entlemen:	
ollowing is a notice of intentiton to do certain work a	
Amerada Petroleum Corporation Company or Operator Lease	State "O" Well No. 4 in NET NET
Sec. 30 , T. 19 , R. 37	, N. M. P. M., Monument Field,
LeaCounty.	
cemented by the Halliburton method wi	
Easing and fittings will be test undisturbed for thirty minutes. If no be drilled out of casing and the same undisturbed for thirtym minutes. If no beauthous the same undisturbed for thirtym minutes.	welded casing was set in this well at 2505° an
Easing and fittings will be test undisturbed for thirty minutes. If no be drilled out of casing and the same undisturbed for thirty minutes. If resumed.	welded casing was set in this well at 2505° and th 500 sackd of cement. ed with 1200# pump p essure and allowed to store of drop in pressure results cement plug will the test of 1200# again applied and allowed to store
Easing and fittings will be test undisturbed for thirty minutes. If no be drilled out of casing and the same undisturbed for thirtym minutes. If no resumed. MAY: 136	welded casing was set in this well at 2505° and th 500 aackd of cement. ed with 1200% pump p essure and allowed to stood of the pressure results cement plug will the test of 1200% again applied and allowed to stone drop in pressure results, drilling will be Amerada Petroleus Corporation
Easing and fittings will be test undisturbed for thirty minutes. If no be drilled out of casing and the same undisturbed for thirtym minutes. If no resumed. MAY: 136	welded casing was set in this well at 2505° and th 500 aackd of cement. ed with 1200% pump p essure and allowed to stood of the pressure results cement plug will the test of 1200% again applied and allowed to stone drop in pressure results, drilling will be
Easing and fittings will be test undisturbed for thirty minutes. If no be drilled out of casing and the same undisturbed for thirtym minutes. If no resumed. MAY: 136	welded casing was set in this well at 2505° and th 500 aackd of cement. ed with 1200% pump p essure and allowed to stood of the pressure results cement plug will the test of 1200% again applied and allowed to stone drop in pressure results, drilling will be Amerada Petroleus Corporation
Easing and fittings will be test undisturbed for thirty minutes. If no be drilled out of casing and the same undisturbed for thirtym minutes. If no resumed. MAY: 136	welded casing was set in this well at 2505° and th 500 aackd of cement. ed with 1200# pump p essure and allowed to stood of the pump pessure results cement plug will the test of 1200# again applied and allowed to stone drop in pressure results, drilling will be Amerada Petroleum Corporation Company or Operator
Easing and fittings will be test undisturbed for thirty minutes. If no be drilled out of casing and the same undisturbed for thirty minutes. If no resumed.	welded casing was set in this well at 2505° and th 500 aackd of cement. ed with 1200% pump p essure and allowed to stood of one in pressure results cement plug will the test of 1200% again applied and allowed to stone drop in pressure results, drilling will be Amerada Petroleum Corporation Company or Operator By Ja Manager
Easing and fittings will be test undisturbed for thirty minutes. If no be drilled out of casing and the same undisturbed for thirty minutes. If resumed.	welded casing was set in this well at 2505' and th 500 aackd of cement. ed with 1200# pump p essure and allowed to stood drop in pressure results cement plug will the test of 1200# again applied and allowed to stone drop in pressure results, drilling will be company or operator By Ja Market Position Farm Boss
Easing and fittings will be test undisturbed for thirty minutes. If no be drilled out of casing and the same undisturbed for thirtym minutes. If no resumed. MAY 136 oproved	welded casing was set in this well at 2505' and th 500 sackd of cement. ed with 1200# pump p essure and allowed to stood of one in pressure results cement plug will the test of 1200# again applied and allowed to stone drop in pressure results, drilling will be Amerada Petroleum Corporation Company or Operator By Ja Marky Position Farm Boss Send communications regarding well to

1 1.18

Mark Room (MARK) Mark Mark Room (1997) And Administration (1997)

 $(x_1, x_2, \dots, x_n) = \sum_{i=1}^n (x_i, x_i) + \sum_{i=1}^n (x_i, x_i) = \sum_{i=1}^n (x_i, x_i) + \sum_{i=1}^n (x_i, x_i) = \sum_{i=1}^n (x_i, x_i) =$

 $x = \frac{1}{2} \left(\frac{1}{$

• . 4.0