

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-1533 1/2	

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Conoco Inc.	8. Farm or Lease Name STATE AC COM
3. Address of Operator P. O. Box 460, Hobbs, New Mexico 88240	9. Well No. 2
4. Location of Well UNIT LETTER <u>C</u> <u>660</u> FEET FROM THE <u>NORTH</u> LINE AND <u>1980</u> FEET FROM THE <u>WEST</u> LINE, SECTION <u>30</u> TOWNSHIP <u>19-S</u> RANGE <u>37-E</u> NMPM.	10. Field and Pool, or Wildcat EUNICE MONUMENT <u>1/4</u>
15. Elevation (Show whether DF, RT, GR, etc.)	12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>
REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> SHUT OFF WATER, OPEN ADD'L PAY	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1708.

MIRU 2/25/84. SPOTTED 6 SXS CAL-SEAL + 3 SXS CLASS "C" w/TOC @ 3870'. DO TO 3915'. SET RBP @ 3886'. SPOTTED 1 BBL 15% ACID 3800'-3880'. PERF w/2 JSPF @ 3850'-3872' (34 PERFS). SET PKR @ 3800'. ACIDIZED w/37 BBLs 15% HCL-NE-FE. FLUSHED w/24 BBLs TFW. SWRD. REL PKR. TESTED. MIRU 5/3/84. SPOTTED 4 SXS CLASS "H" w/TOC @ 3916'. RAN PROD EQUIP. PMPD 0 BO, 276 BW, 0 MCF IN 24 HRS 5/16/84.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u>Wm A. Butterfield</u>	TITLE <u>Administrative Supervisor</u>	DATE <u>8/8/84</u>
ORIGINAL SIGNATURE		
APPROVED BY <u> </u>	TITLE <u> </u>	DATE <u>AUG 10 1984</u>

UNCLASSIFIED

AUG - 9 1984

U.S. AIR FORCE
HOBBS OFFICE