

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

JUN 15 1936 AM

AREA 640 ACRES
LOCATE WELL CORRECTLY

THE OHIO OIL COMPANY,

P. O. BOX 00, HOBBS, NEW MEXICO.

Company or Operator
THE OHIO OIL COMPANY Well No. **2** in **NESE** of Sec. **30**, T. **19**
Lease
R. **37**, N. M. P. M., **Monument** Field, **Lea** County.
Well is _____ feet south of the North line and _____ feet west of the East line of _____
If State land the oil and gas lease is No. **B-5553** Assignment No. _____
If patented land the owner is _____, Address _____
If Government land the permittee is _____, Address _____
The Lessee is _____, Address _____
Drilling commenced **4-13** **1936** Drilling was completed **5-16** **1936**
Name of drilling contractor **Noble Drilling Co.,** Address **Tulsa, Okla.**
Elevation above sea level at top of casing **3616** feet.
The information given is to be kept confidential until _____ 19____.

OIL SANDS OR ZONES

No. 1, from **3800** to **3940** No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from _____ to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13"O.D. 50				144	Reg.			
9-5/8 40				1294	Float			
7 24				3790	"			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15 1/2	13	144	150	Halliburton	10	50
12 9-5/8	1294	500	Halliburton	10	50	
9-3/4	7	3790	400	Halliburton	10	50

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____
Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment **No results**

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from **0** feet to **3940** feet, and from _____ feet to _____ feet
Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing **May 29,** **1936**
The production of the first 24 hours was **50** barrels of fluid of which **100** % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____
If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____
Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Jack Clark, Driller **R. C. Lindsay**, Driller
Bruce Harp, Driller _____, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **11th**
day of **June**, 19**36**
R. M. Jensen
Notary Public.

My Commission expires _____

Place _____ Date _____
Name **Glenn Rush**
Position **Supt.**
Representing **The Ohio Oil Co**
Company or Operator
Address **P.O. Box 00, Hobbs, N.M.**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	50	50	Caliche
50	85	35	Sand
85	150	65	Red Beds
150	368	218	R. B. & shells
368	610	242	R. B. & Redrock
610	780	170	R. B. & Red Rock
780	997	217	Blue shellstreaks & R. B. shells
997	1092	95	R. R. shale & gyp
1092	1159	67	R.R. hard sand & shell
1159	1237	78	R. R. & streaks of sand
1237	1249	12	Broken R. R. & Anhydrite
1249	1255	6	Red Rock
1255	1325	70	Anhydrite
1325	1380	55	Broken Anhydrite & salt
1380	1435	55	Salt
1435	1608	173	Salt & Anhydrite
1608	2410	802	Salt & Str. Anhydrite.
2410	2450	40	Anhydrite
2450	2492	42	Anhydrite & Gyp.
2492	2563	71	Anhydrite & Str. Gyp.
2563	2686	123	Anhydrite
2686	2747	61	Brown Sandy lime
2747	2828	81	Anhydrite & lime.
2828	2855	27	Lime.
2855	2945	90	Lime & Anhydrite.
2945	2972	27	Lime & Str. Gyp.
2972	3045	73	Anhydrite & lime.
3045	3071	26	Lime
3071	3138	67	Anhydrite & lime.
3138	3160	22	Lime & Str. of Gyp.
3160	3226	66	Lime & Broken Anhydrite.
3226	3252	26	Lime, Sdy. show gas
3252	3278	26	Lime & Anhydrite
3278	3284	6	Lime, gas
3284	3293	9	Lime
3293	3325	32	Gray & Br. lime. Oil odor.
3325	3349	24	Lime
3349	3420	71	Gray lime.
3420	3442	22	Lime.
3442	3482	40	Lime & Br. lime streaks
3482	3520	38	Lime.
3520	3541	21	Gray lime.
3541	3715	159	Lime.
3700	3715	15	Sdy. lime, show gas
3715	3759	44	Lime.
3759	3800	41	B. lime show Gas & Oil
3800	3817	17	B. lime oil odor
3817	3834	17	Gray lime, gas
3834	3845	11	Sandy lime
3845	3886	41	Brown lime, saturated
3886	3923	37	Lime, streaks sand, show gas.
3923	3940	17	Lime & hard gray streaks, Oil.