

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on squeezing Perforations	X

November 17, 1948

Date

Monument, New Mexico.

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation Phillips 8 "A" Well No. 3 in the \_\_\_\_\_  
Company or Operator Lease  
SW 1/4 NE 1/4 of Sec. 31, T. 19S, R. 37E, N. M. P. M.,  
Monument, Field, Lea County.

The dates of this work were as follows: November 16, 1948

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on November 13, 19 48  
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3905' Drilled out depth, Set Baker Model K Magnesium Retainer @ 3883' and broke formation w/ 4000# Pressure and broke down to 2000# with 4 bbls mud, mixed 50 Sacks El Toro Common cement and pumped to spot w/ 28 bbls mud flush, and cement hit formation w/ 3600# Pressure and broke down to 2000# and built back up to 4000# and held there, squeezed 36 bbls cement into formation, 2 sacks on top of retainer and reversed out 12 sacks cement, waited 14 hours and picked up drill pipe and drilled out cement to 3880' and will gun perforate with Lane-Wells from 3870' to 3880'

Witnessed by Don Topper, Amerada Pet. Corp., Asst. Dist. Supt.  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

17 day of November 19 48Name Don TopperWill Hailer Taylor

Notary Public

Position Asst. Dist. Supt.Representing Amerada Pet. Corp.,  
Company or Operator

My commission expires \_\_\_\_\_

Address Drawer D, Monument, New Mexico.

Remarks:

Ray Zumbach  
Name  
Title

ROVED

3-11-1948

