JCJSN

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

District Office					
DISTRICT I P.O. Box 1980, Hobbs NM 88241-1980 OI	L CONSERVATIO		WELL API NO.		
DISTRICT II	2040 Pacheco St. Santa Fe, NM 87505		30 - 025 - 05773 5. Indicate Type of Lease		
P.O. Drawer DD, Artesia, NM 88210 DISTRICT III			STATE FEE X		
1000 Rio Brazos Rd., Aztec, NM 87410 6.				is Lease No.	
SUNDRY NOTICES AND REPORTS ON WELLS					
DIFFERENT RESERVOIR. USE APPLICATION FOR FERMIT			1	7. Lease Name or Unit Agreement Name NORTH MONUMENT G/SA UNIT	
1. Type of Well: OIL GAS			BLK 15	ar or or	
WELL WELL	OTHER INJE	CTION			
2. Name of Operator Amerada Hess Corporation			8. Well No.		
3. Address of Operator 9. Pool				Wildcat IENT G/SA	
4. Well Location Unit LetterC	Feet From The NORTH	Line and 23	1) Feet Fro	m The	WEST Line
Section : 31	Cownship 19S Ra	nge 37E	NMPM	LEA	County
	10. Elevation (Show whether	1150			
11. Check Approx	oriate Box to Indicate	Nature of Notice.	Report, or (Other Date	/ <i>////////////////////////////////////</i>
NOTICE OF INTE	•	1	SEQUENT		
	51.115 4.115 4.51415011				[
	PLUG AND ABANDON L	REMEDIAL WORK		ALTERING C	[
	CHANGE PLANS L	COMMENCE DRILLING		PLUG AND A	BANDONMENT L
PULL OR ALTER CASING —		CASING TEST AND CE			Г
OTHER:		OTHER: CUNYER	TO INJECTION	ON WELL	
 Describe Proposed or Completed Operations work) SEE RULE 1103. 	(Clearly state all pertinent deta	ails, and give pertinent da	tes, including estim	ated date of sta	rting any proposed
1-6-98 THRU 1-19-98 MIRU DAWSON WELL SVC. & STAR BOP & TOH W/TBG. TIH W/6-1/3 W/7" MD. G RBP & SET AT 3743 DUMPED 3 SKS. SAND ON TOP RB W/NEW WELLHEAD. RE-INSTALLED LATCHED ONTO & TOH W/RBP. T CEMENT RETAINER FR. 3814' - 1	8" BIT, TAGGED CEMENT R '. TESTED CSG. TO 540 P. REMOVED BOP. REMOV D BOP. TIH W/RETRIEVIN IH W/6-1/8" BIT & TAGGE	RETAINER AT 3814' PSI FOR 30 MIN. PED OLD WELLHEAD & IG HEAD, WASHED SA ID RETAINER AT 381	HEAD, INSTALL & TOH. TIH HELD OK. REPLACED ND OFF RBP, 4'. DRLD.	ED	
CIRC. HOLE CLEAN. WESTERN A 3838' W/300 GRAIN PRIMER CORI W/2 SPF, TOTAL 33 SHOTS, FR.	TLAS RAN GR/CNL & CCL L D. TIH W/4" EXPANDABLE 3780' - 3797'.	OGS. STRING SHOT CSG. GUN & PERFO CONTI	OH FR. 3807'	-	1)
I hereby certify that the information above is true and					
SIGNATURE OUTTOURS	TITL	E STAFF ASSIST.		DATE	1-23-1998
TYPE OR PRINT NAME COLLEEN ROBINSON				TELEPHONE NO.	915-758-6778
ing − in visit (nit in the interest	5 20,0 4,46 8 XX X	E			4 1998
CONTREIONS OF ARMONIAL IE ANY.	/// // // // // // // // // // //	-	· 	> \\ \ \	

D &

TIH W/6-1/8" BIT & DRLD. FR. 3845' - 3880'. CIRC. HOLE CLEAN. SWABBED WELL. FRACMASTER ACIDIZED PERFS. & OH FR. 3763' - 3798' & 3823' - 3880' W/3000 GAL. 15% HCL ACID. SWABBED WELL. TIH W/7" ARROWSET PKR ON 2-3/8" POLY LINED TBG. & SET PKR. AT 3734' W/8000# TENTION. CIRC. PKR. FLUID. PRESS. TESTED & CHARTED CSG. TO 540 PSI FOR 30 MIN. HELD OK. REMOVED BOP & INSTALLED WELLHEAD. RDPU & CLEANED LOCATION. WELL CLOSED IN FOR INSTALLATION OF INJECTION LINE. C-103 TO FOLLOW ON FIRST INJECTION.