

Orig: & cc: OCC
cc: FHR
JTR
FNEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work reported is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

January 24, 1955
(Date)Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Co.

J. R. Phillips "B"

(Company or Operator)

(Lease)

Gackle Drilling Company

Well No. 5 in the SW 1/4 NW 1/4 of Sec. 31

(Contractor)

Lea

T. 19 S, R. 37 E, NMPM, Durant Pool, County.

The Dates of this work were as follows:

6-26-54

Notice of intention to do the work (was) (was not) submitted on Form C-102 on _____, 19_____,
(Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

ID 3550, set 5 1/2" OD casing @ 3550 and cemented with 1,000 sacks of cement. Ran temperature survey which indicated top of cement back of 5 1/2 casing @ 1080' from surface. Let cement set 72 hours and tested with 1000# pump pressure for 30 minutes before and after drilling plug. No decrease in pressure. Drilled cement plug to 3517'. Ran PGM electric log. Perforated 5 1/2" casing with 2 jet shots per foot from 3322 to 3380, 3386 to 3396, 3422 to 3430, 3436 to 3446, 3452 to 3461, 3469 to 3476, 3480 to 3497. Ran 3496' of 2" UE tubing. Acidized with 1,000 gallons of mud acid. Maximum pressure of 2,000# . Completed as gas well 7-6-54 @ 3,500 MCF per 24 hours.

Well shut in at completion. No gas connection at this date, 1-24-55

Witnessed by: Ira L. Wagner
(Name)Sinclair Oil & Gas Co.
(Company)Assistant foreman
(Title)

Approved: OIL CONSERVATION COMMISSION

S. J. Stanley
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: G. C. Allen

Position: Dist. Supt.

Representing: Sinclair Oil & Gas Co.

Address: 520 East Broadway, Hobbs, New Mexico

on the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861

at the 1st of June 1861