

Orig: &amp; cc: OCC

cc: VDA

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

RECEIVED

Form C-103  
Revised 7/1/52

DEC 1 1953

OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS HOBBS-OFFICE

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	<input checked="" type="checkbox"/>
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

11-21-53

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil &amp; Gas Company

(Company or Operator)

J. R. Phillips "A"

(Lease)

Mobile Inc.

(Contractor)

Well No. 7 in the SE 1/4 SW 1/4 of Sec. 31

T. 19, R. 37, NMPM, Monument Blinberry Pool, Lea County.

The Dates of this work were as follows: Nov. 2, 1953 to Nov. 17, 1953

Notice of intention to do the work (was) (was not) submitted on Form C-102 on Nov. 2, 1953.

(Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Original Total Depth 5714 - Plugback depth 5678

Set Retainer @ 5623 and pumped 300 sacks in formation at 1900#. Squeezed with 100 Sacks @ 4500#. Drilled cement plug to 5690. Perforated from 5673 to 5683. Swabbed dry. Acidized W/500 Gallons of mud acid, squeezed 3 Bbls. in formation. Flowed 284 Bbls. of new oil and 450 Bbls. of water in 24 hours. Squeezed off perforations with 100 sacks cement. Drilled plug to 5678, perforated 5673 to 5678, swabbed dry. Acidized W/500 Gal. of 15% acid, 3 Bbls. in formation. Swabbed well dry. Acidized W/500 Gal. of 15% acid, swabbed 33 Bbls. oil in 15 Hrs. 32 Bbls. new oil next 24 Hrs. Acidized W/1000 Gal. of 15% acid, swabbed 117 Bbls. of new oil and 149 Bbls. of water in 14 Hrs. After three day interval took test of 240 Bbls. oil and 144 Bbls. water in 24 Hrs. thru 20/64" choke.

Witnessed by J. J. Wright, Jr.

(Name)

Sinclair Oil &amp; Gas Co.

(Company)

Foreman

(Title)

Approved:

OIL CONSERVATION COMMISSION

J. J. Stanley

(Name)

Engineer District 1

(Title)

DEC 1 1953

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Position Dist. Supt.

Representing Sinclair Oil &amp; Gas Co.

Address Box 1927 Hobbs, N.M.