

# OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

RECEIVED  
OCT 1 1949  
NORTH OIL FIELD

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	<input checked="" type="checkbox"/>
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

September 29, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation

D.F. Larsen

Well No. 4 in the

Company or Operator

Lease

SW<sub>1</sub> of the NE<sub>1</sub>

of Sec. 32

T. 19

R. 37

N. M. P. M.,

Monument

Field,

Lea

County.

The dates of this work were as follows: September 19, 1949

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on September 19 19 49 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3902' - Total Depth. 6-5/8" OD Casing set at 3795'

Cut 6-5/8" OD Casing off at 3062' with Baash-Ross Cutting Tool. Pulled out 98 Jts. of 6-5/8" OD Casing. Ran back in hole w/ wash pipe and conditioned hole. Pulled wash pipe and ran back with 100 Jts. of 6-5/8" OD Casing in good condition, with 7-5/8" OD x 6-5/8" ID x 4' Long Baash-Ross Casing Bowl to make splice with casing remaining in hole. Tested casing with 1400# pressure for 1/2 hour and there was no pressure drop. Circulated hole clean, ran tubing and swabbed well in. In 9 hours well flowed 148.41 bbls. fluid, 4% water. GOR 1558. Work-over complete.

Witnessed by E.E. Shirley

Name

Amerada Petroleum Corp.

Company

Head Gauger

Title

Subscribed and sworn before me this

13

day of

Dec.

1949

I hereby swear or affirm that the information given above is true and correct.

Name

D.F. Topp

Position

Assistant District Superintendent

Representing

Amerada Petroleum Corporation

Company or Operator

My commission expires

10/24/53

Address

Drawer "D", Monument, New Mexico

Remarks:

Roe. Yankrough  
Title

APPROVED

DEC 1 1949

Title