NEW XICO OIL CONSERVATION COM SSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INDESIMAN MA OTTOOM OF
	X NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	
Monument, New	Mexico February 11, 1937
OIL CONSERVATION COMMISSION,	······
Santa Fe, New Mexico.	
Gentlemen: Following is a notice of intention to do certain work as described below at the	
Company or Operator of Sec. 32 T. 19 R. 37	Lease ,N. M. P. M., Monument
A& County.	, , , , , , , , , , , , , , , , , , , ,
FILL DETAILS OF	PROPOSED PLAN OF WORK
-5/8" 32 # 8-Thd. New Seamless casin	ules and regulations of the commission ng was set in this well at 2493' and cement
-5/8" 32 # 8-Thd. New Seamless casing the Halliburton Method with 600 sach as ingand fittings will be tested with adisturbed for thirty minutes. If no hen be drilled out of the casing and gain be applied and allowed to stand	ng was set in this well at 2493' and cement be 1200# pump pressure and allowed to stand drop in pressure results the cement will the same test of 1200# pump pressure will undisturbed for thirty minutes. If no drop
-5/8" 32 # 8-Thd. New Seamless casing the Halliburton Method with 600 sach as ingand fittings will be tested with a ndisturbed for thirty minutes. If no hen be drilled out of the casing and gain be applied and allowed to stand a pressure results the drilling will the standard of the casing will the standard of the case of the case of the case of the standard of the case of th	ng was set in this well at 2493' and cement is 1200# pump pressure and allowed to stand drop in pressure results the cement will the same test of 1200# pump pressure will undisturbed for thirty minutes. If no drop then be resumed.
-5/8" 32 # 8-Thd. New Seamless casing the Halliburton Method with 600 sach as ingand fittings will be tested with a ndisturbed for thirty minutes. If no then be drilled out of the casing and gain be applied and allowed to stand an pressure results the drilling will the drilling wil	ng was set in this well at 2493' and cement be 1200# pump pressure and allowed to stand drop in pressure results the cement will the same test of 1200# pump pressure will undisturbed for thirty minutes. If no drop
-5/8" 32 # 8-Thd. New Seamless casing the Halliburton Method with 600 sach as ingand fittings will be tested with a ndisturbed for thirty minutes. If no then be drilled out of the casing and gain be applied and allowed to stand an pressure results the drilling will the drilling wil	ng was set in this well at 2493' and cement is 1200# pump pressure and allowed to stand drop in pressure results the cement will the same test of 1200# pump pressure will undisturbed for thirty minutes. If no drop then be resumed. Amerada Petroleum Corporation
asingand fittings will be tested with ndisturbed for thirty minutes. If no then be drilled out of the casing and to gain be applied and allowed to stand an pressure results the drilling will to approved	ng was set in this well at 2493' and cement is 1200# pump pressure and allowed to stand drop in pressure results the cement will the same test of 1200# pump pressure will undisturbed for thirty minutes. If no drop then be resumed. Amerada Petroleum Corporation Company or Operator
asingand fittings will be tested with ndisturbed for thirty minutes. If no then be drilled out of the casing and to gain be applied and allowed to stand an pressure results the drilling will to approved	ng was set in this well at 2493' and cement is 1200# pump pressure and allowed to stand drop in pressure results the cement will the same test of 1200# pump pressure will undisturbed for thirty minutes. If no drop then be resumed. Amerada Petroleum Corporation Company or Operator By Lakey
32 # 8-Thd. New Seamless casing by the Halliburton Method with 600 sach as ingand fittings will be tested with undisturbed for thirty minutes. If no then be drilled out of the casing and tagain be applied and allowed to stand an pressure results the drilling will except as follows:	ng was set in this well at 2493' and cement is 1200# pump pressure and allowed to stand drop in pressure results the cement will the same test of 1200# pump pressure will undisturbed for thirty minutes. If no drop then be resumed. Amerada Petroleum Corporation Company or Operator By Amerada Petroleum Corporation Company or Operator By Amerada Petroleum Corporation Company or Operator By Amerada Petroleum Corporation
3-5/8" 32 # 8-Thd. New Seamless casing by the Halliburton Method with 600 sach as ingand fittings will be tested with undisturbed for thirty minutes. If no then be drilled out of the casing and again be applied and allowed to stand an pressure results the drilling will approved	ng was set in this well at 2493' and cement 1200# pump pressure and allowed to stand drop in pressure results the cement will the same test of 1200# pump pressure will undisturbed for thirty minutes. If no drop then be resumed. Amerada Petroleum Corporation Company or Operator By Amerada Petroleum Corporation Send communications ragarding well to
3-5/8" 32 # 8-Thd. New Seamless easing the Halliburton Method with 600 sackasing and fittings will be tested with undisturbed for thirty minutes. If no then be drilled out of the easing and again be applied and allowed to stand in pressure results the drilling will	ng was set in this well at 2493' and cement is 1200# pump pressure and allowed to stand drop in pressure results the cement will the same test of 1200# pump pressure will undisturbed for thirty minutes. If no drop then be resumed. Amerada Petroleum Corporation Company or Operator By Lakey

108