100

NEW ZXICO OIL CONSERVATION COM 3SION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

cions of the Commission. Indicate nature of	notice by checking below:
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
OTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
COTICE OF INTENTION TO DEEPEN WELL	
Monument, New 1	Mexico February 22, 1937
IL CONSERVATION COMMISSION, anta Fe, New Mexico. entlemen: ollowing is a notice of intention to do certain work as	described below at the
Amerada Petrole um Corporation Company or Operator	Larsen5 Well No. 4 in SW NE
	Lease Monument Field.
5-5/8" 20# 10-Thd. New Seamless casing	es and regulations of the commission was set in this well at 3795° and cemented to
FOLLOW INSTRUCTIONS IN THE RUL 3-5/8" 20# 10-Thd. New Seamless casing the Halliburton Method with 100 sacks. Casing and fittings will be tested with andisturbed for thirty minutes. If no be drilled out of the casing and the sa applied and allowed to stand undisturbed	was set in this well at 3795° and cemented to 1200# fump pressure and allowed to stand drop in pressure results the cement will then ame test of 1200# pump pressure will again be not thrity minutes. If no drop in pressure
FOLLOW INSTRUCTIONS IN THE RUL 3-5/8" 20# 10-Thd. New Seamless casing the Halliburton Method with 100 sacks. Casing and fittings will be tested with andisturbed for thirty minutes. If no be drilled out of the casing and the sa applied and allowed to stand undisturbed	was set in this well at 3795° and cemented to 1200# fump pressure and allowed to stand drop in pressure results the cement will then ame test of 1200# pump pressure will again be not thrity minutes. If no drop in pressure
FOLLOW INSTRUCTIONS IN THE RUL 3-5/8" 20# 10-Thd. New Seamless casing the Halliburton Method with 100 sacks. Casing and fittings will be tested with indisturbed for thirty minutes. If no be drilled out of the casing and the sa applied and allowed to stand undisturbed results the drilling will then be resum	was set in this well at 3795° and cemented by 1200% frump pressure and allowed to stand drop in pressure results the cement will then ame test of 1200% pump pressure will again be sed for thrity minutes. If no drop in pressure
FOLLOW INSTRUCTIONS IN THE RUL 5-5/8" 20# 10-Thd. New Seamless casing the Halliburton Method with 100 sacks. Casing and fittings will be tested with undisturbed for thirty minutes. If no be drilled out of the casing and the sa applied and allowed to stand undisturbe results the drilling will then be resum	was set in this well at 3795' and cemented to 1200# pump pressure and allowed to stand drop in pressure results the cement will then ame test of 1200# pump pressure will again be not for thrity minutes. If no drop in pressure med. Amerada Petroleum Corporation Company or Operator By J. G. Stankey Position Farm Boss
FOLLOW INSTRUCTIONS IN THE RUL 6-5/8" 20# 10-Thd. New Seamless casing the Halliburton Method with 100 sacks. Casing and fittings will be tested with undisturbed for thirty minutes. If no be drilled out of the casing and the sapplied and allowed to stand undisturbed results the drilling will then be resumptively.	Amerada Petroleum Corporation Amerada Petroleum Corporation Company or Operator By July Company or Operator
6-5/8" 20# 10-Thd. New Seamless casing the Halliburton Method with 100 sacks. Casing and fittings will be tested with undisturbed for thirty minutes. If no be drilled out of the casing and the sapplied and allowed to stand undisturber results the drilling will then be resum	was set in this well at 3795' and cemented by 1200# pump pressure and allowed to stand drop in pressure results the cement will then ame test of 1200# pump pressure will again be not drop thrity minutes. If no drop in pressure med. Amerada Petroleum Corporation Company or Operator By J. G. Stankey Position Farm Boss