STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

40. OF COPIES SECEIVED	T	
MOLTUBLATEID	1	
SANTA FE		
FILE		
U.1.0.1.		
LAND OFFICE		
OPERATOR		

OIL CONSERVATION DIVISION

DISTRIBUTION	P. O. BO		Form C-103 Revised 10-1-7
FILE	SANTA FE, NEV	V MEXICO 87501	
U.S.O.S.			Sa. Indicate Type of Lease
LAND OFFICE			State X Foe
OPERATOR			5. State Oil & Gas Lease No.
CLUID			mmmmmm
SUNUR SUNUR THIS FORM FOR PRO THE TAPPLICATE	Y NOTICES AND REPORTS ON POSALS TO DRILL ON TO DETPEN OR PLUGION FOR PERMIT - " IFORM C-101) FOR SU	WELLS	
[1.	04 704 PERMIT = 170KM C-1(01) FOR SU	LH PROPOSALS.)	7. Unit Agreement Name
OIL GAS WELL X	OTHER-		7. O.M. Agreement Hume
2. Name of Operator			8. Farm or Lease Name
Amerada Hess Corporatio	n		State "II"
3. Address of Operator			9. Well No.
Drawer D, Mon ument, Ne	w Mexico 88265		1
4. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTERE	1980 FEET FROM THE North	LINE AND660 FEET I	Eumont Yates 7R Oveen
What	22		
THE WEST LINE, SECTIO	N 32 TOWNSHIP 195	RANGE 37E	лем. (
	15. Elevation (Show whether	DF, RT, GR, etc.)	12. County
	/////	3592' DF	Lea ()
Check A	ppropriate Box To Indicate N		
NOTICE OF IN			ENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPCRAFILY ABANDON		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CABING	CHANGE PLANS	CASING TEST AND CEMENT JOB	(c 4)
OTHER	[-]	отнея Zone abandonm	ent (Eumont) X
OTHER .			1
17. Describe Proposed or Completed Ope work) SEE RULE 1103.	rations (Clearly state all pertinent deta	ils, and give pertinent dates, includ	ling estimated date of starting any proposed
		•	
January 15 to January 21	., 1980		
Dulled claid date 2 1/2			
Pulled & laid down 3-1/2	"tbg. & pkr. Ran retri	evable bridge plug & p	okr. Set bridge plug at
cement retainer on 2-3/8	press. Held OK. Dumped	1 4 SKS. sand on top of	f bridge plug. Ran
cement retainer on 2-3/8 6-5/8" csg. perf. fr. 33	22' to 3559' w/200 ske	BILTURE Woodstierne	zed Eumont zone thru
neat cement. Pumped 503	sks. cement into format	ion left 55 sks com	at incide 6 5/0"
below retainer, 2 sks. a	bove retainer & reverse	Tout 40 sks WOC s du	ald goment incide
0-3/0 csg. 11. 3137, to	3195', drid. retainer a	at 3195' & hard cement	fr 31001 to 25201 c
celletic stringers to 3339	· Ran bit to 3589' & t	ested someoze job w/85	50# press. Held OK.
Trip out w/bit. Ran tbg	. & recovered bridge plu	ig. Eumont zone P&A.	on press. Herd on.
	_		
:			
18. I hereby certify that the information ab	ove is true and complet best of	my knowledge and belief.	
OBD.			
IGNED WHITE		upv. Adm. Ser.	
DAS SIGNAL			
Westry De 201			FFR 19 1980

OIL CONSERVATION DIV.

EE8 18 .80

BECEINED