NET MEXICO OIL CONSERVATION CC VISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR
NOTICE OF INTENTION TO CHANGE PLANS	X NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
NOTICE OF INTENTION TO DEEPEN WELL	
Monument, New	Mexico July 25, 1936 Place Date
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen:	Date
	an describe 2.1.
Following is a notice of intentiton to do certain work as described below at the. Amerada Petroleum Corporation State 7117	
Company or Operator Lease	State "U" Well No. 1 in SW NW.
of Sec. 32 , T. 19 , R. 37	, N. M. P. M., Molament Fie
County.	
FILL DETAILS OF T	DDOROGHD Training
FOLLOW INSTRUCTIONS IN THE	PROPOSED PLAN OF WORK
	LES AND REGULATIONS OF THE COMMISSION
y the Halliburton Method with 180 sacks	Was set in this well at 185' and cemented
Cement will be drilled out of the old allowed to stand undisturbed for one cain to determine if any water has come	
Cement wall be drilled out of the old allowed to stand undisturbed for one cain to determine if any water has come	casing and the hole widl be bailed to bottom hour. The bailer will then be run to bottom mulated. If no water has accumulated the
Cement will be drilled out of the old allowed to stand undisturbed for one ain to determine if any water has some	casing and the hole wial be bailed to bottom
Cement will be drilled out of the old allowed to stand undisturbed for one cain to determine if any water has come	casing and the hole widl be bailed to bottom a hour. Thebailer will then be run to bottom mulated. If no water has accumulated the
Cement will be drilled out of the old allowed to stand undisturbed for one ain to determine if any water has some	casing and the hole widl be bailed to bottom hour. The bailer will then be run to bottom mulated. If no water has accumulated the
Cement wall be drilled out of the old allowed to stand undisturbed for one cain to determine if any water has come	casing and the hole widl be bailed to bottom hour. The bailer will then be run to bottom mulated. If no water has accumulated the
Cement will be drilled out of the old allowed to stand undisturbed for one cain to determine if any water has come	casing and the hole widl be bailed to bottom a hour. Thebailer will then be run to bottom mulated. If no water has accumulated the
Cement wall be drilled out of the old allowed to stand undisturbed for one cain to determine if any water has accurately will be resumed.	casing and the hole widl be bailed to bottom hour. The bailer will then be run to bottom unulated. If no water has accumulated the
Cement will be drilled out of the old allowed to stand undisturbed for one gain to determine if any water has accurately for the control of t	casing and the hole widl be bailed to bottom a hour. Thebailer will then be run to bottom mulated. If no water has accumulated the
Cement will be drilled out of the old allowed to stand undisturbed for one ain to determine if any water has accurately stand will be resumed.	Amerada Petroelum Corporation
Cement will be drilled out of the old allowed to stand undisturbed for one gain to determine if any water has accurately will be resumed.	Amerada Petroelum Corporation Company or Operator
Cement will be drilled out of the old allowed to stand undisturbed for one gain to determine if any water has accurately stand will be resumed.	Amerada Petroelum Corporation Company or Operator By Casing and the hole widt be bailed to bottom Water has accumulated the
Cement will be drilled out of the old allowed to stand undisturbed for one gain to determine if any water has accurately will be resumed.	Amerada Petroelum Corporation Company or Operator By Position Position Position Position Position Position Parm Boss
Cement will be drilled out of the ond allowed to stand undisturbed for one gain to determine if any water has accurately resumed. pproved	Amerada Petroelum Corporation Company or Operator By Position Farm Boss Send communications regarding well to